

K-Type Thermometer

Features:

- CE-Mark approval
- Portability and simplicity one-hand operation
- Highly accurate thermometer
- 0.3% °C/°F accuracy
- With MAX/DATA HOLD function
- User-selective 0.1°/1° resolution
- With K-type bead thermocouple
- Overload protection 24VAC/VDC
- Carrying case
- Valox housing to withstand accidental drops

Model: Stix600


Applications:

- Greenhouse
- Office environment
- Labs
- Environment studies
- Weather monitoring
- Art galleries/Museums
- Department store
- Workshops

Specifications:

Display: 3½digit liquid crystal display (LCD) with a maximum reading of 1999.

Zero: Automatic.

Low battery indication: The "  " is displayed when the battery voltage drops below the operating level.

Measurement rate: 2.5 times/second.

Operating environment: 0°C to 50°C, <70% R.H..

Storage environment: -20°C to 60°C, 0 to 80% R.H. with battery removed from meter.

Accuracy: Stated accuracy at 23°C±5°C, <75% R.H..

Dimensions: 170mm(H) x 44mm(W) x 40mm(D).

Weight: Approx. 140g including battery (1.5Vx4pcs AAA size).

Temperature:

Range: -40°C to 1350°C, -40°F to 2000°F

Accuracy: ±(0.3%rdg + 1°C) on -50°C to 1000°C

±(0.5%rdg + 1°C) on 1000°C to 1300°C

±(0.3%rdg + 2°F) on -58°F to 2000°F

