

Carbon Monoxide Meter

Features:

- CE-Mark approval
- Portability and simplicity one-hand operation
- Display Back-Light feature
- CM by a reading on the LCD and a beeper tone
- With MAX/DATA HOLD function
- Valox housing to withstand accidental drops
- Carrying case


Model: Stix670

Applications:

- Indoor
- Outdoor
- Office environment
- Labs
- Environment studies
- Garage
- Fireplace
- Exhaust
- Heating engine

Specifications:

Display: 3½digit liquid crystal display (LCD) with a maximum reading of 1999.

Low battery indication: The "  " is displayed when the battery voltage drops below the operating level.

Operating environment: 0°C to 50°C, <70% R.H..

Storage environment: -20°C to 60°C, 0 to 80% R.H. with battery removed from meter.

Accuracy: Stated accuracy at 23°C±5°C, <75% R.H..

Dimensions: 202mm(H) x 44mm(W) x 40mm(D).

Weight: Approx. 160g including battery (1.5VX4pcs AAA size).

CM:

Range: 0 to 1000PPM

(2000PPM with 5 minute max exposure time.)

Sensor Calibration: Factory calibrated on 205ppm

Sensor Type: Electrochemical (specific to CM)

Initial Accuracy: ±5% of reading ±5PPM

Response time: <70sec to 90% of reading

Operating relative humidity: 15 to 90%RH

Long term drift: <5% / year (depending on use)

Battery life: 200 hours typical

No measurable current draw when in " off " position

