

Manometer

Features:


- CE-Mark approval
- Portability and simplicity one-hand operation
- Display Back-Light feature
- Auto zero by power on
- MAX/DATA HOLD function
- User-selective resolution 0.01"/0.1"
- Valox housing to withstand accidental drops
- Carrying case

Applications:

- Gas flow pressure measurement
- Pressure measurement in air conditioning systems

Specifications:

Display: 3½digit liquid crystal display (LCD) with a maximum reading of 1999.

Low battery indication: The "  " is displayed when the battery voltage drops below the operating level.

Operation environment: 0°C to 50°C, <70%R.H.

Storage environment: -20°C to 60°C, 0 to 80% R.H. with battery removed from meter.

Accuracy: Stated accuracy at 23°C±5°C, <75% R.H..

Dimensions: 190mm(H) x 44mm(W) x 40mm(D).

Weight: Approx. 150g including battery (1.5VX4pcs AAA size).

Manometer:

Sensor: Solid State

Range: 0-20" water column

Accuracy: ±2.0% full scale

Resolution: 0.01"

Operating Temperature: 32 to 105°F

Operating relative humidity: 15 to 90%RH, non-condensing

Battery life: 150 hours typical

No measurable current draw when in " off " position

Model: Stix680

