

**Make sure to visit  
our Website**  
http://www.sefram.fr



# SEFRAM 7862HDT2

## State-of-Art Specifications for High Definition TV

### Capabilities :

- Panoramic 7 inch LCD coloured screen
- Weight: 2,1kg
- Display free to air programs for digital terrestrial, cable and satellite
- Display High Definition TV programs MPEG4-H264
- Full measurements DVB-T2, DVB-T/H, DVB-C, DVB-S and DVB-S2
- Full measurements for MPEG-2 and MPEG-4
- Ultra fast spectrum analysis
- Satcheck mode with NIT (satellite recognition)
- Real time echoes and pre-echoes measurement with zoom
- Constellation diagram with zoom
- Memorise and export/import data with USB memory stick
- Battery with 1 hour charging time and 4 hours autonomy
- Rugged carrying case
- Water proof front panel with sensitive button
- Optional PC software to create reports



**SEFRAM 7862HDT2**

### All digital measurements

The SEFRAM 7862HDT2 provides all necessary measurements for DVB-T2, DVB-T/H, DVB-C, DVB-S and DVB-S2. The panoramic TFT display will show all parameters and measurements for the selected channel.

### Specific features to save time

Time is money! With the ultra fast spectrum analysis, NIT, Check sat mode, autoset, real time echoes, constellation diagram, impulse response, MER versus carrier (DVB-T and T2) the SEFRAM 7862HDT2 will save your precious time during antenna setup.

### Easy to use

Direct access to functions makes the SEFRAM 7862HDT2 intuitive and very easy to use. Getting started with the TV meter is like a game.

### Optimized design for your safety

With only 2,1kg, the SEFRAM 7862HDT2 will be the ideal companion for all your measurements on the field. Its compact size will provide better safety and makes your work easier.

### Panoramic Display

With its panoramic 7 inch LCD screen (16:9), the reading of measurements will be easier than any other product available on the market.

### HD TV display with all digital sounds decoding

The new SEFRAM 7862HD displays high definition TV programs (MPEG4-H264) with the **decoding of all digital sounds in standard**, including Dolby, Dolby Digital, AAC and HE-AAC.

	<b>7861</b>	<b>7861HDT2</b>	<b>7862HDT2</b>	<b>7865HDT2</b>	<b>7866HDT2</b>
Frequency Band	Terrestrial 45-865MHz Satellite 950-2150MHz	Terrestrial 45-865MHz Satellite 950-2150MHz	Terrestrial 45-865MHz Satellite 950-2150MHz	Terrestrial 5-865MHz Satellite 950-2150MHz	Terrestrial 5-865MHz Satellite 950-2150MHz
DVB-T/H	✓	✓	✓	✓	✓
DVB-S, DVB-S2	✓	✓	✓	✓	✓
DVB-C			✓ (45-865MHz)	✓	✓
TV MPEG2 display	✓	✓	✓	✓	✓
TV MPEG4 - H264 display (HD TV)		✓	✓	✓	✓
Fast spectrum analysis	✓	✓	✓	✓	✓
Check sat mode with NIT	✓	✓	✓	✓	✓
Constellation diagram with zoom			✓	✓	✓
Graphical display of measurements				✓	✓
OSD, Audio & video PID				✓	✓
Wifi measurements *	✓*	✓*	✓*	✓*	✓*
TS-ASI Input/Output				✓	✓
GPS					✓

\* with optional adapter





# SEFRAM 7862HDT2

Panoramic TV Meter

Specifications	Terrestrial band			Satellite band	
<b>Frequency</b>	45-865 MHz			950-2150 MHz	
Range	measure 25 kHz, display 1 kHz			measure 25 kHz, display 1 kHz	
Resolution					
<b>Level measurements</b>	20-120 dBµV			30-110 dBµV	
Dynamic range	5dBµV typical				
Noise floor level	dBµV, dBmV, dBm, V			dBµV, dBmV, dBm, V	
Units	±2dB +/- 0.05dB/°C			±2dB +/- 0.05dB/°C	
Accuracy	0.1dB			0.1dB	
Resolution	automatic with selected standard 100 - 300 kHz			1MHz	
Filters	B, G, D, K, I, L, M, N, FM, carrier, DVB-C, DVB-T/H, DVB-T2			PAL, SECAM, NTSC, DVB-S, DVB-S2, DSS	
Standards	V, C/N, Noise margin, V/A1, V/A2 according to selected standard			RF, C/N, link margin	
Measurements					
<b>Digital measurements</b>	<b>DVB-T/H</b>	<b>DVB-T2</b>	<b>DVB-C</b>	<b>DVB-S</b>	<b>DVB-S2</b>
Bit Error Rate (BER)	CBER (before Viterbi) VBER (after viterbi) UNC (lost packets)	LDPC, BCH, FER (frame error)	BER (before Reed Solomon) JNC (lost packets)	CBER, VBER, UNC	LDPC, BCH, PER
Modulation Error Rate (MER)	5 - 35dB	5 - 35dB	20 - 40dB	0-20dB	
Symbol rate	-	-	1 to 7.224 Ms/s	1 to 45Ms/s	
Bandwidth	6MHz, 7 MHz, 8 MHz	5MHz, 6MHz, 7 MHz, 8 MHz	-	-	
Mode	-	SISO, MISO, single and multi PLP	-	-	
FFT size	2k and 8k, auto and manual	1k, 2k, 4k, 8k, 16k and 32k + bandwidth extension, auto	-	-	
Constellation	QPSK, 16 and 64QAM, auto	QPSK, 16, 64 and 256QAM auto	16, 32, 64, 128 and 256QAM	QPSK and 8PSK	
Code rate	1/2, 2/3, 3/4, 5/6, 7/8 (auto)	1/2, 3/5, 2/3, 3/4, 4/5, 5/6 (auto)	-	QPSK DVB/S: 1/2, 2/3, 3/4, 5/6, 6/7, 7/8 (auto) QPSK DVB-S2: 2/5, 1/2, 3/5, 2/3, 3/4, 5/6, 8/9, 9/10 (auto) 8PSK DVB-S2: 3/5, 2/3, 3/4, 5/6, 8/9, 9/10 (auto)	
Guard interval	Automatic and manual	Automatic	-	-	
Inverted spectrum	Manual	Automatic	-	-	
Standard	ETS 301-701	ETS 302-755	ITU J83-Appendix A and B	ETS 300-421	ETS 302-307
<b>Pre-echoes / Echoes / Impulse response</b>					
Dynamic range	30 dB, 75km (in 8k)	50 dB, -75km +75km (in 8k)	-	-	
Units	µs, km, miles	µs, km, miles	-	-	
	<b>NICAM</b>				
Frequency	45-865MHz / Level measurement			-	
Standard	B, G, D, K, I, L			-	
<b>Fast spectrum analysis</b>					
Ultra fast mode	100 ms typ. (10 times/s)			350 ms typ. (10 times/s)	
Filters (automatic with selected span)	100kHz, 300kHz, 1 MHz			1MHz, 3MHz, 10MHz	
Attenuator	automatic with selected frequency (0 to 50 dB with 10 dB steps)			automatic (0 to 50 dB with 10 dB steps)	
Dynamic (display)	60 dB (10 dB/div)			60 dB (10 dB/div)	
Span	5 MHz to full span in 1, 2, 5 steps			5 MHz to full span in 1, 2, 5 steps	
<b>Measurement map</b>					
Capacity				scrolling 11 programs	
Display				graphical (bargraph)	
<b>Check sat mode</b>					
				fast search of satellite, single or double LNC, with NIT	
				30 satellites typical, with European database loaded	
				4 transponders per satellite, can be modified by user	
<b>Memory</b>					
Saving	internal, non volatile memory, USB stick (not supplied with)				
Data	places, measure (level, BER/MER, frequency map, Spectre,...)				
Capacity	320 Ko (1000 files max or folders)				
<b>TV picture and sounds</b>					
Analogue programs	yes (PAL, SECAM, NTSC)			-	
Digital programs	(free to air) SD (standard definition MPEG2) and HD (high definition MPEG4 / H,264)			-	
Sounds	analogue, MPEG-1, MPEG-2, AAC, HE AAC, Dolby® Digital, Dolby® Digital Plus			-	
Digital programs (*)	yes			yes	
<b>RF input</b>					
Input	75 Ohm, F and BNC with adaptor supplied				
Max permissive voltage	80 V DC, 80 V rms/50Hz				
<b>Auxiliary inputs and outputs</b>					
Interfaces	2 x USB (A and mini B), 10baseT Ethernet (RJ45)				
Power supply input	jack 5,5 mm, 15 V max, 5 A max				
Audio / Video	Input/Output audio (0dBm) and video (1Vrms)				
<b>Remote supply and control</b>					
Voltage	5V/13V/18 V/24V, 500 mA max (300mA for 24V)			13/18 V, 500 mA max	
DiSEqC	-			DiSEqC 1.2, dish rotor control, committed & uncommitted switches	
Mini DiSEqC	-			22 kHz, toneBurst	
SatCR	-			DiSEqC protocol extension, control of 8 slots max.	
<b>General Specifications</b>					
Display	LCD TFT Couloured 7 inch (178mm) 16/9, backlighted, 800x480 dots (W-VGA)				
Power supply	main adaptor 110/230 VAC, jack 5,5mm, 15 V 5 A				
Battery (non removable)	LiOn battery 70Wh				
Autonomy	3 hours typical				
Built-in charger	1 hour charging time for 80% capacity				
Operating temperature	-5°C to 45°C				
Storage temperature	-10°C to 60°C				
EMC and safety	EN 55022-A2 / EN 61326-1 / EN 61010-1				
Dimensions	210 x 90 x 297 mm				
Weight	2,1 kg (including battery and pouch)				

**Supplied with :** main adaptor (90-245V with European plug), user's manual on CD ROM, F/F and F/BNC adaptor

**Optional accessories :** Wifi adaptor: P/N 978651000  
Pouch for accessories: P/N 978656500  
KitTR7836: kit with TR7836 software (CD-ROM) and USB cable  
Car cigarette lighter power supply: P/N 978361000

Dolby is a trade mark of Dolby Laboratories.



(\*) the display of digital encrypted programs is possible, if user has a valid subscription card and if the encryption type is supported by the TV Meter. Please check with our sales department when ordering.  
FT7862HDT2A00- Specifications can be updated without notice



32, rue Edouard Martel • B.P. 55 • 42009 - St Etienne cedex 2



Fax. +33 (0).4.77.57.23.23

Web : www.sefram.fr • e-mail : sales@sefram.fr

## For assistance and ordering



**Metrix Electronics Limited**

Minchens Court, Minchens Lane,  
Bramley, RG26 5BH, U.K.  
Tel:+44 (0)845 034 3234, Fax:+44 (0)845 034 3233  
E-mail: sales@metrix-electronics.com  
Web: www.metrix-electronics.com