

Thermal Graphics Printers



- Print text, measured data, statistics and graphics on 'document proof' paper
- Status and fault reports, test and calibration tickets
- Quiet, long-life thermal print head
- Ideal for use with controllers, PLCs, DPMs, counters, message displays, etc.
- Add date & time automatically. Print pre-stored messages and add variable data (IPP 144-40 GE)
- Paper re-roll accessory (IPP-AW) for archive printouts and optional IP64 cover

IPP 144-40 G printer features

Prints up to 48 alphanumeric characters per line (Standard-Mode) on 80mm wide paper
 Choice of many language character sets, including IBM international
 Normal or inverse printout options
 Multi-standard opto-isolated serial interface for RS 232, RS 422, RS 485 or TTY
 DIN-standard metal housing 144 x 72 mm bezel size
 Hinged front panel for easy paper roll replacement, with LED paper-out indication
 Print interval timer adjustable from 10 sec to 24 hours

IPP 144-40 GE additional features of enhanced version

Real-time clock/calendar with easy Summer/Winter change
 Date & time can be added automatically or triggered by serial interface control character
 Memory to store up to 15 40-character pre-programmed texts with variable insert feature
 Additional USB, RS 232, RS 485 or Profibus interface (Interface 2). Paper out alarm relay.

Stocked by RS Components Ltd

Model	Interface 2	Supply Voltage	RS Stock No.
IPP144-40G	None	12V DC	-----
		24V DC	478-0570
		110-230V AC	478-0564
IPP144-40GE USB	USB **	12V DC	-----
		24V DC	478-0609
		110-230V AC	-----
Accessories			
IPP-AW	Paper re-roll unit		229-330
Cover	For IPP & IPP-AW combination		229-346
Thermal Paper	10 roll pack		623-013

** RS232, RS485 & Profibus interfaces not stocked by RS

Full specifications: www.metrix-electronics.com/HTML/P2E_thermal_panel_printers.html

IPP144-40G-GE_1011