

Release Date: September 2008

Metrix Electronics Ltd, Precision Enterprise House, Rankine Road, Daneshill West, BASINGSTOKE RG24 8PP. U.K.
Tel: +44 (0)1256 864150 Fax: +44 (0)1256 864154 Email: sales@metrix-electronics.com Web: www.metrix-electronics.com



NEW

Compact Process and Temperature Data Recorders

The new **SRD-99** series are compact 96x96mm panel mounting data recorders to record and display process signals in numeric, tabular or graphical format. They are available in 1, 4 or 8-channel versions; with either temperature (Pt100/500/1000), or 0/4...20mA process control loop inputs. Each input can be named, scaled and captioned by the installer – using the simple touch key operated menu.

Data recording can be automatic or externally controlled by a digital input, with programmable sample intervals from one second up to one hour. The internal memory is up to 8MB (up to 2 million points), but can be significantly extended when a USB memory stick is connected. For example, a 1GB stick can record 8-channels every second for over one year (250 million points).

All versions also have an RS-485 (Modbus RTU) serial port for configuration using the supplied **S-Toolkit** Windows® software, and data transfer to the **Loggy Soft** data analysis and archiving software. With the USB option, data can also be downloaded and transferred by a USB flash memory stick.

A lockable clear plastic door accessory is available to prevent unauthorised operation and provide environmental protection to IP 42 standards.

Click link below for data sheet and user manual:

www.metrix-electronics.com/HTML/P2G_compact_data_recorders.html

***** ENDS *****