





7859 FIELD STRENGTH METER

USER MANUAL

This product contains one or more programs protected under international and US copyright laws as un-published works. They are confidential and proprietary to Dolby laboratories. Their reproduction or disclosure, in whole or in part, or the production of derivative works there from without the express permission of Dolby Laboratories is prohibited. Copyright 2003-2005 by Dolby Laboratories. All rights reserved.

Revision follow-up

Version / Date	Modified chap- ters	Detail of change/update
1.0 / March 2017	All	First document created

Thank you for purchasing this SEFRAM product and therefore trusting our company. Our different teams (research department, production, sales department, after-sales service...) are aiming at satisfying your wishes by designing and updating very advanced appliances.

To obtain the best performance from this product please read this manual carefully.

For more information please contact our different services

04 77 59 01 01

E-mail Sales department:	sales@sefram.fr
E-mail After-sales:	sav@sefram.fr
E-mail Technical support:	support@sefram.fr
Fax:	+33 (0)4 77 57 23 23
Web:	www.sefram.fr



Copyright Sefram, 2017. All rights reserved. Any total or partial reproduction of this document must be submitted for Sefram written authorization.

GUARANTEE

Your instrument is guaranteed for two years for labor and parts against any manufacturing defect and/or functioning hazard. This guarantee extends from the delivery date and ends 730 calendar days later.

In case of guarantee contract, this will cancel or replace these guarantee conditions hereabove.

The guarantee conditions by SEFRAM are available on the website <u>www.sefram.com</u>. The general guarantee conditions should prevail on the following conditions that they sum up.

This guarantee does not cover the result of any abnormal use, handling mistake or mistake in the storage conditions outside the defined range.

In case of application of the guarantee, the user shall return, at its own expenses, the relevant appliance to our factory:

SEFRAM Instruments & Systèmes

Service Après-vente

32, Rue Edouard MARTEL

BP 55

42009 SAINT-ETIENNE CEDEX 2

And add a description of the observed breakdown to the appliance.

The standard supplies provided with the appliance (cables, outlets...), the consumables (batteries ...) and the optional supplies (suitcases...) are guaranteed for 3 months against any manufacturing defect.

Such items as a suitcase, a LCD screen or a touchpad are guaranteed only for a normal use.

The guarantee does not cover wearing, accidental breaks or consecutive to a shock or any abnormal use.

The factory options integrated to the appliance are guaranteed for the same duration as the appliance itself.

In case of replacement or repair of the product, the remaining guarantee duration shall be:

- The remaining duration of the guarantee if the appliance is still under guarantee
- If the guarantee duration is less than 90 days, the replaced part is guaranteed for 90 days

Any replacement part becomes the property of the user and the exchanged parts become the property of SEFRAM.

In case of intervention by an insurance company, the product becomes the property of the insurance company upon its exclusive request. Else, it shall remain property of the user.

The guarantee covers exclusively the materials manufactured and provided by SEFRAM.

Any intervention by the user or any third party without prior authorization by the company voids the guarantee.

The user shall be responsible for the return of its appliance to our site. Hence, it shall provide for a conditioning that shall correctly protect the appliance while shipping. It shall subscribe, at its own expenses, any insurance required for the transport.

The SEFRAM company reserves the right to refuse any product wrongly conditioned and not to take in charge any break consecutive to the transport.

Particular case of the battery: There is a Li-ion battery as a standard equipment of this appliance. It shall not be transported outside the appliance. In no case shall the user replace it. Its replacement in the factory is necessary to check the charge system and the protective securities.

What to do in case of malfunction?

In case of malfunction or for any advice for use, please contact the technical support by SEFRAM Instruments & Systèmes: 0825 56 50 50 / 2

A technician shall answer you and give you any information required to solve your problem.

What to do in case of failure?

In case of failure of your appliance, please contact the technical support: $0825\ 56\ 50\ 72$

Some advice! Some technical help!

SEFRAM Instruments & Systèmes commits itself to help you on the phone about the use of your appliance. Please call or Technical Support:

04 77 59 01 01

Or e-mail:

support@sefram.fr

We thank you for your trust.

METROLOGY

The meteorological conditions of your measurement instrument are defined in the specifications of this notice. Climate and environmental conditions restrict the specifications of your Field Strength Measurer (MDC). SEFRAM checks the characteristics of each appliance one by one on an automatic bench during its manufacture. The adjustment and control are guaranteed under conditions of the ISO9001 certification by facilities in connection with the COFRAC (or equivalent in the context of ILAC reciprocity).

The specified characteristics are considered stable for a period of 12 months from the first use under normal conditions of use.

We recommend a check after 12 months and max. 24 months of use, then every 12 months after 24 months.

For any check of the characteristics, the following average climate conditions shall be maintained $(23^{\circ}C \pm 3^{\circ}C - 50(\pm 20)\% RH)$. The MDC should have been working for 0,5 hour before check.

We recommend that you have this control made by our after-sales service (Service Après-Vente) for the best service and preservation of the measuring quality of your instrument.

When a MDC returns to SEFRAM, maximum service is provided with internal updating according to the required adjustments and software updates. In case of shift in the characteristics, your instrument shall be adjusted to recover its original characteristics.

PACKAGING

The packaging of this product is fully recyclable. Its design allows the transport of your instrument under the best possible conditions. Please note that the original packaging should be additionally wrapped in case of transport by air, road or postal.

SPARE PARTS

According to the consumption law of March 17, 2014, Article L111-3 and Decree 2014-1482 of 09/12/2014, SEFRAM informs you of the availability of spare parts of products placed on the market as of March 1, 2015:

Spare parts are not available to the consumer. SEFRAM offers the supply of spare parts during repair by its service.

Consumable parts are provided according to the legislation applicable to them (case of batteries).

SEFRAM is committed to providing parts or alternatives for a period of at least 2 years beyond the warranty period.

TABLE OF CONTENTS

1	Imp	portant information	.9
1	1.1	Particular precautions	9
1	.2	Security instructions	9
1	.3	Symbols and definitions	9
1	.4	Conformity and restrictions of the appliance	10
2	Qui	ick start-upŕ	11
2	2.1	Presentation of the appliance	11
2	2.2	Signal spotting	12
	2.2.	1 Scanning a terrestrial antenna in RF mode	12
	2.2.2	2 Installation of a terrestrial antenna	14
	2.	.2.2.1 Use of the spectrum	14
	2.	.2.2.2 Use of the Antenna pointing	16
	2.2.3	3 Installation of a satellite dish	18
3	Pre	esentation	21
3	3.1	General	21
3	3.2	Description of the appliance	22
4	Ρο	wer-up	23
2	11	Battery	23
2	1.2	Battery charge	23
2	1.3	External power supply	24
2	1.4	Turning the appliance on and off	24
5	Ma	n-machine interface	25
Ę	5 1	Content of the screen	25
Ę	5.2	Changing name or value	27
-	<u> </u>	1 Changing inside a table	27
	5.2.2	2 Change with selection	28
	5.2.3	3 Change with virtual keyboard	28
Ę	5.3	Lists of measurements and setup library	29
6	AU	TOSET mode	32
f	5.1	Terrestrial mode	33
6	5.2	Satellite mode	33
6	5.3	Cable Mode	34
6	6.4	«START » menu key	34
7	Me	asurement lists	36
	7 1	The list page	36
7	 7.2	Modification of a list	37
8	Set	tun library	40
.	201 2 1	The library nage	۲ ۰
c و	2.1 2.2	Creation or modification of setups in the library	40 40
۰ ۲	<u>с</u> г	ack Sat	12
9			+3
ç	9.1 NG	Updating satellites	44
ç	9.2	Check Sat function	44
ç	1.3	Checking the aligned satellite	46

9.4.1 Recall 47 10 TERRESTRIAL check
10 TERRESTRIAL check
11 The Measures-TV-Spectrum page 51 12 Measures (MEASURES-TV-SPECTRUM) 52 12.1 Autolock function 52 12.2 Modification of parameters 53 12.3 Level measurements 53 12.4 Satellite band 54 12.5 Terrestrial band 55 12.6 Thresholds 55 12.7 Digital measurements 56 12.8 DVB-T/H 57 12.9 DVB-T2 /T2 Lite 58 12.10 DVB-C 59 12.11 DVB-C2 60 12.12 DVB-S et DSS 61 12.13 DVB-S2 62 13 Spectrum analyzer 63 14 Image and Sound 64 14.1 Digital TV 64 14.2 Full screen mode 64 14.3 Audio 65 14.4 Table of services 65 15.1 Terrestrial band 66 15.2 Satellite band 67 15.2 Natellite band 67 15.2 Natellite band 67
12 Measures (MEASURES-TV-SPECTRUM) 52 12.1 Autolock function 52 12.2 Modification of parameters 53 12.3 Level measurements 53 12.4 Satellite band 54 12.5 Terrestrial band 55 12.6 Thresholds 55 12.7 Digital measurements 56 12.8 DVB-T/H 57 12.9 DVB-T2 /T2 Lite 58 12.10 DVB-C 59 12.11 DVB-C2 60 12.12 DVB-S2 62 13 Spectrum analyzer 63 14 Image and Sound 64 14.1 Digital TV 64 14.2 Full screen mode 64 14.3 Audio. 65 15.4 Table of services 65 15.1 Terrestrial band 66 15.2 Satellite band 67 15.2 Power ON 67
12.1 Autolock function 52 12.2 Modification of parameters 53 12.3 Level measurements 53 12.4 Satellite band 54 12.5 Terrestrial band 55 12.6 Thresholds 55 12.7 Digital measurements 56 12.8 DVB-T/H 57 12.9 DVB-T2 /T2 Lite 58 12.10 DVB-C 59 12.11 DVB-C2 60 12.12 DVB-S et DSS 61 12.13 DVB-S2 62 13 Spectrum analyzer 63 14 Image and Sound 64 14.2 Full screen mode 64 14.3 Audio 65 15.4 Terrestrial band 65 15.4 Terrestrial band 66 15.2 Satellite band 67 15.2.1 Power ON 67
12.2 Modification of parameters 53 12.3 Level measurements 53 12.4 Satellite band 54 12.5 Terrestrial band 55 12.6 Thresholds 55 12.7 Digital measurements 56 12.8 DVB-T/H 57 12.9 DVB-T2 /T2 Lite 58 12.10 DVB-C 59 12.11 DVB-C2 60 12.12 DVB-Se et DSS 61 12.13 DVB-S2 62 13 Spectrum analyzer 63 14 Image and Sound 64 14.2 Full screen mode 64 14.3 Audio 65 14.4 Table of services 65 15.4 Terrestrial band 66 15.2 Satellite band 66 15.2 Satellite band 67 15.2.1 Power ON 67
12.3 Level measurements 53 12.4 Satellite band 54 12.5 Terrestrial band 55 12.6 Thresholds 55 12.7 Digital measurements 56 12.8 DVB-T/H 57 12.9 DVB-T2 /T2 Lite 58 12.10 DVB-C 59 12.11 DVB-C2 60 12.12 DVB-S et DSS 61 12.13 DVB-S2 62 13 Spectrum analyzer 63 14 Image and Sound 64 14.2 Full screen mode 64 14.3 Audio 65 14.4 Table of services 65 15.1 Terrestrial band 66 15.2 Satellite band 66 15.2 Satellite band 67 15.2.1 Power ON 67
12.4 Satellite band 54 12.5 Terrestrial band 55 12.6 Thresholds 55 12.7 Digital measurements 56 12.8 DVB-T/H 57 12.9 DVB-T2 /T2 Lite 58 12.10 DVB-C 59 12.11 DVB-C2 60 12.12 DVB-S et DSS 61 12.13 DVB-S2 62 13 Spectrum analyzer 63 14 Image and Sound 64 14.2 Full screen mode 64 14.3 Audio 65 15.4 Terrestrial band 66 15.1 Terrestrial band 66 15.2 Satellite band 67 15.2.1 Power ON 67
12.5 Terrestrial band
12.6 Thresholds 55 12.7 Digital measurements 56 12.8 DVB-T/H 57 12.9 DVB-T2 /T2 Lite 58 12.10 DVB-C 59 12.11 DVB-C2 60 12.12 DVB-Set DSS 61 12.13 DVB-S2 62 13 Spectrum analyzer 63 14 Image and Sound 64 14.1 Digital TV 64 14.2 Full screen mode 64 14.3 Audio 65 14.4 Table of services 65 15 Remote power supply / LNB – DiSEqC 66 15.1 Terrestrial band 66 15.2 Satellite band 67 15.2.1 Power ON 67
12.7 Digital measurements 56 12.8 DVB-T/H 57 12.9 DVB-T2 /T2 Lite 58 12.10 DVB-C 59 12.11 DVB-C2 60 12.12 DVB-S et DSS 61 12.13 DVB-S2 62 13 Spectrum analyzer 63 14 Image and Sound 64 14.2 Full screen mode 64 14.3 Audio 65 14.4 Table of services 65 15 Remote power supply / LNB – DiSEqC 66 15.2 Satellite band 67 15.2.1 Power ON 67
12.8 DVB-T/H
12.9 DVB-T2 /T2 Lite 58 12.10 DVB-C 59 12.11 DVB-C2 60 12.12 DVB-S et DSS 61 12.13 DVB-S2 62 13 Spectrum analyzer 63 14 Image and Sound 64 14.1 Digital TV 64 14.2 Full screen mode 64 14.3 Audio 65 14.4 Table of services 65 15.1 Terrestrial band 66 15.2 Satellite band 67 15.2.1 Power ON 67
12.10 DVB-C
12.11 DVB-C2
12.12 DVB-S et DSS
12.13 DVB-S2
13 Spectrum analyzer 63 14 Image and Sound 64 14.1 Digital TV 64 14.2 Full screen mode 64 14.3 Audio 65 14.4 Table of services 65 15 Remote power supply / LNB – DiSEqC 66 15.1 Terrestrial band 66 15.2 Satellite band 67 15.2.1 Power ON 67
14 Image and Sound 64 14.1 Digital TV 64 14.2 Full screen mode 64 14.3 Audio 65 14.4 Table of services 65 15 Remote power supply / LNB – DiSEqC 66 15.1 Terrestrial band 66 15.2 Satellite band 67 15.2.1 Power ON 67
14.1 Digital TV
14.2 Full screen mode
14.3 Audio
14.4 Table of services
15 Remote power supply / LNB – DiSEqC 66 15.1 Terrestrial band 66 15.2 Satellite band 67 15.2.1 Power ON 67
15.1 Terrestrial band
15.2 Satellite band 67 15.2.1 Power ON 67
15.2.1 Power ON
15.2.1 Switches
15.2.1 Positioner
15.2.2 DCSS
15.2.2.1 Influence of the DCSS on the spectrum analyzer
16 Constellation74
17 Echo / Guard interval
18 Measurement map77
18.1 Out of tolerance values
19 Optic measurement
19.1 Presentation of the optic measurement 70
19.2 What you need to know
19.2.1 The optical fiber
19.2.2 Connectors
19.3 Optical power measurement
19.4The satellite reception via optical fiber

19.5	Fiber reception after coupler	84
20 Conf	iguration	
20.1	Language	
20.2	Frequency map	85
20.3	Memories	86
20.3.1	View	87
20.3.2	Save	
20.3.3	Update	
20.4	Factory recovery	
20.5	Configuration import/export	90
21 Softw	vare update	91
22 Save		92
23 Con	nection of the appliance to a PC	93
24 Disp	layed messages	95
24.1	Alert messages	95
24.2	Error messages	96
25 Main	tenance	97
26 Tech	nical specifications	
26.1	Technical specifications	
26.2	Digital measurements	
26.3	OPTIC MEASUREMENT	101
26.4	Miscellaneous	102
26.5	General specifications	
26.6	Accessories	
26.7	V, dB μ V, dBmV and dBm conversion	104
26.8	Typical values for measurements	104
27 Term	inology	
28 CE C	eclaration	. Erreur ! Signet non défini.

1 Important information

Please read carefully the following instructions before using your appliance.

1.1 Particular precautions

- Do not use the product for any other use than specified.
- Use the provided charger unit to prevent any deterioration of the appliance and guarantee its measurement characteristics.
- Do not use in a wet environment.
- Do not use in an explosive environment.
- In case of failure or for the maintenance of the appliance, only a qualified personal shall be entitled to work on it. In such a case, it is required to use Sefram spare parts.
- Do not open the appliance: risk of electric shock.
- You should use the F/F adaptor provided with your measuring instrument. Any other adaptor could damage your appliance and jeopardizes the guarantee.
- Do not use gloves, stylus or any other object on to the touchscreen. Handle the screen carefully.

1.2 Security instructions

For a correct use of the appliance, it is necessary that users abide by the security and use instructions described in this manual.

Specific warnings appear all along this manual.

In case of need, warning symbols are displayed on the appliance:

1.3 Symbols and definitions

Symbols in this manual:



Remark: Shows important information



Key or press zone

Window or display zone showing up after the operation achieved



Symbols on the appliance:



Attention: Refer to the manual. Shows a risk of damage for the material connected to the instrument or to the instrument itself.



Ground: Grounded accessible parts.



Product for recycling.

1.4 Conformity and restrictions of the appliance

See chapter EC Declaration of conformity.

2 Quick start-up

2.1 Presentation of the appliance



To plug the appliance for optic measurements, refer to the paragraph <u>19.1 Presentation of the optic measurement</u>

Important keys:

7859 is an appliance with a capacitive touchscreen. This requires a soft handling. No glove and no stylus should be used, so that the triggering should be taken into account.

You will recognize the « keys » by their dark grey color (example: the home key:

You may also access tables by pressing lines (on white or yellow)

0	0	DIGITAL+ ASTRA 1	10729 VL	DVB-S2 22000	
0	1	ARD ASTRA 1	10743 HL	DVB-S 22000	
0	2	ANIXE HD ASTRA 1	10773 HL	DVB-S2 22000	
0	3	DIGITAL+ ASTRA 1	10788 VL	DVB-S 22000	
\bigcirc	4	DIGITAL+ ASTRA 1	10817 VL	DVB-S2 22000	

Welcoming page:



Gives you access to the using mode (RF or optic)

. .



Attention : To exit a window like in this example below, press the key:



2.2 Signal spotting

The 7859 appliance tracks very quickly RF or optical terrestrial or satellite signals.

In the following chapter, we will see how to spot a RF signal on three types of installation:

- Checking of a terrestrial antenna (the installation has already been made).
- Installation of a terrestrial antenna.
- Installation of a satellite dish.

2.2.1 Scanning a terrestrial antenna in RF mode

In this case, the Autoset function allows a scan of the channels that the antenna detects. Plug the cable of your antenna to the 7859 appliance (WARNING: use an adequate adaptor)

The antenna shall be previously adjusted to a terrestrial emitter.

Turn on your appliance. Press RF/Optic

Press Entrée RF



The Home page appears on screen. Press Autoset Autoset On this page, press Mode, Terrestrial, then select DVB-T and 8MHz (as here below)

The scan should range from the E21 to the E69 channels, frequency range Europe (you may reduce the number of channels to scan if you know the range of the emitter where the antenna points at: the scan will be faster)



Autoset	VDC= 0.0V	Autoset	VDC= 0.0V IDC= 0mA
Mode: Terrestrial		Mode: Terrestrial	
Frequency map France		Frequency map France	
DVB-T DVB-T2		VB-T DVB-T2	
1.7 5 MHz 6 MHz 7 MHz	8 MHz	1.7 5 MHz 6 MHz 7 MHz	8 MHz
channel: E21 to channel: E60		channel: E21 to channel: E60	
Start		Start	

Press START. The appliance searches until the end of the scan and turns directly to the Measurement plan mode. If channels were found, the appliance makes measurements continuously (C/N-level, then BER/MER) on the detected channels. If no channel has been found, see the next chapter.



To finish, press the home measurement key then on the new page, press Prog, select the channel that you want to display.

Check the level, the BER/MER, the TV detection and the spectrum of the signal on this page...





2.2.2 Installation of a terrestrial antenna

You have two methods to install a terrestrial antenna:

- Use of the spectrum
- Use of the satellite dish

2.2.2.1 Use of the spectrum

Plug the cable of your antenna to the 7859 (take care to use an adequate adaptor)

Turn your appliance on. Press the Measures-TV-Spectrum key

Measures-TV-Spectrum

Press the Spectrum zone, access to terrestrial mode if needed

Marc										VDC	- 0 (v —
Iviea	sures	_	_		_	_	_	_	_	IDC=	Om	ià 🗖 👘
	AUTOSET	>		C		>						
	610.000 MHz	>	1	DVB-1	ſ/ H							
<	E38	>		8 MHz								
Cell	ID:0x3420 (1334	14)										
											_'	J.
RF	51.2 dBµ\	20	40)	60		80		100	1	20	
C/N	30.8 dE	30	10)	20		30		40		50	
BERi	< 3E-8	3 1	E-1	1E-3		1E-5		1E-7		1E-9	Ĩ	4
BERo	• < 9E-9	9 1	E-1	1E-3		1E-5		1E-7		1E-9		<u> </u>
PER	< 9E-0	6 1	E-1	1E-3		1E-5		1E-7		1E-9		
MER	33.8dE	B15	20		25		30		35		40	
LKM	12.8dE	30	10)	20		30		40		50	



Access to full SPAN mode







Adjust the antenna to get the most powerful signal possible

Press directly the signal you want in the spectrum (the cursor moves to where you press)



Press the NIT key the device find automatically all the parameters of the signal. Once the search ended, the device display the "Network Name" and the "Network ID".

Press the Measures-TV-Spectrum key. You can now display the level, the BER/MER of the signal selected on the same page...

Meas	sures									VDC IDC=	= 0.0V = 0mA	+
	AUTOSET	۶	K	С	:0	>						
	610.000 MHz	>		DVB-	T/H							\boldsymbol{k}
	E38	>		8 MH:	z							
Cell	D:0x3420 (1334	4)					-			•		
RF	51.2 dBμV	20	4	10	60		80		100	•	120	
C/N	30.8 dB	0	1	0	20		30		40		50	
BERi	< 3E-8	1	E-1	1E-3		1E-5		1E-7		1E-9		<u></u>
BERo	< 9E-9	1	E-1	1E-3		1E-5		1E-7		1E-9		`
PER	< 9E-6	1	E-1	1E-3		1E-5		1E-7		1E-9		
MER	33.8dB	15	2	:0	25		30		35		40	
LKM	12.8dB	0	1	0	20		30		40		50	

2.2.2.2 Use of the Antenna pointing

The appliance gets an "Antenna pointing" mode in order to align quickly and easily your terrestrial antenna.

To access to the "Antenna pointing" mode from the HOME page, press The following page appears:



Set your emitter name:







Enter 4 frequencies of the emitter you want to check.



You can find many different French transmitters in an Excel file available on the website of SEFRAM (download section, then database transmitters TNT) or by clicking under the following link:

http://www.sefram.com/telechargement/fichier-de-configuration.html

Ш÷

Antenna pointing Frequency map Europe ST-ETIENNE QU. 92 RF 69 QU. 69 RF 75 QU. 79 RF 72 QU. 89 RF 68 i 778.000 MHz E59 DVB-T/H 8 MHz E40 DVB-T/H 8 MHz DVB-T/H DVB-T/H

Slowly orientate the antenna until hearing the locking melody and getting the best quality



No transmitter found, bad reception quality \rightarrow red smiley

Average reception quality (< 50%) \rightarrow orange smiley

Good reception quality (> 50%) \rightarrow green smiley

2.2.3 Installation of a satellite dish

Connect the satellite dish to the appliance. Activate the remote power supply

To access to the Remote power supply page, press



To switch on the remote power supply, press power supply:

then select **ON** in the page to launch the remote



Off

A green check appears in front of what you validated



Select a satellite like in the example below (here Astra1):



Slowly orientate the satellite dish until hearing the locking melody and getting the best quality





No found transponder \rightarrow red smiley

Average reception quality (< 50%) \rightarrow orange smiley

Good reception quality (> 50%) \rightarrow green smiley



To check if the aimed satellite is the right one: press the NIT key

The appliance searches the MPEG NIT table on one of the 4 transponders and displays the name of the satellite:





115

<u>Attention</u>: The displayed name depends on the content of the MPEG NIT table. Some distributors provide no (or poor) such table. The displayed information may be wrong.

Attention:

To identify a satellite, you must be locked on all 4 transponders. (Quality > 0)
However, some transponders are regularly modified. See the frequency range of the satellite when a transponder does not seem to work.
Some switches or LNB work only with DiSEqC commands. In this case, position the band (OL) and the polarization on DiSEqC at the Configuration page LNB-DiSEqC. (Attention: the Check Sat is slower when using the DiSEqC command).

3 Presentation

3.1 General

-The **7859** field measurer is a handy appliance designed to qualify and maintain all RF or optical installations RF for broadcasting and receiving analogical and terrestrial digital, satellite or cable network television channels.

-The band ranges between **5 MHz and 2200 MHz**; this allows accurate measurements on all analogical television standards, FM carrier waves and the various digital standards DVB-C/C2, DVB-T/T2/T2Lite, DVB-S/S2 and DSS.

-He does Level measurements in average, peak and power according to the selected standard

-Optical power measurements are made on the 3 bands

-Conversion of an optical signal (optical head, FTH-type cable) into a RF signal RF within the band of the field measurer

-In **Measurement Plan** mode, they scan up to 50 setups at the same time and compare them to decision levels (min / max).

- Equipped with an efficient **Bit Error Rate** measurement (various BER, MER), they allow the full validation of digital transmissions DVB-T/T2/T2Lite, DVB-C/C2, DVB-S/S2 and DSS.

- Providing a **Constellation** diagram for digital standards, the detection and display of **Echoes and pre-ech-oes** permit to complete this analysis.

- You can display the **digital terrestrial or satellite TV** (free programs) under SD or HD.

- You can hear digital sound through integrated loudspeakers.

-Designed for use on field, it is compact (less than 2 kg battery included), autonomous (battery pack and quick charger), equipped with a LCD 7" touchscreen (capacitive).

- The high memory content allows the storage of many configurations, measurements and spectrum curves.

-The appliance fully remote-controlled through USB and ETHERNET connections via a computer.



3.2 Description of the appliance

4 Power-up

All the material is checked before shipment and delivered in an adapted packaging. There is no particular unpacking instruction.

The appliance is equipped with a Lithium-Ion (Li-ion) battery.

However, if the appliance has remained idle more than one month long, check its charge state and reload if required.

4.1 Battery



Attention: Any intervention on the battery requires the disassembly of the appliance and should be made by a SEFRAM technician.

Use only batteries provided by SEFRAM.

Security advice:

- → Do not throw into the fire or heat up the battery pack
- → Do not shunt the parts of the battery: risk of explosion!
- ➔ Do not drill
- → Do not disassemble the battery pack
- → Do not reverse the polarities of the battery
- → This battery pack includes a protective item that should not be damaged or removed
- → Protect the pack from the heat while storing
- → Do not damage the protective sheath of the pack
- → Do not store the appliance in a vehicle under sunlight
- → Used batteries are not for domestic waste; lithium batteries should be recycled.

The battery has a 200-charge-discharge cycle life or 2 years.

Advice to extend the life of your battery:

- ➔ Avoid deep discharges
- → Do not store the batteries too long without using them
- → Store the battery around 40% loading
- → Do not fully charge or fully discharge the battery before storage.

When the battery is almost fully discharged, the appliance will warn "Low battery", and then will shut off after a few minutes.

4.2 Battery charge

To charge the battery inside the appliance:

- Connect the external power supply provided through the jack plug of the appliance (above)
- Connect the power supply on the mains
- The internal charger starts loading the battery; the green lamp lights up.



Charge the device only when the device is off. Charge the device only with the provided power supply block.

The battery is 80%-loaded after 1 hour 50 minutes. The total charge is reached after 2 hours 30 minutes. The autonomy is defined in terrestrial mode with the lighting of the screen decreased, without remote supply, interfaces not connected and sound at 10%

4.3 External power supply

The appliance works under 15V (1 A) power supply. The power supply block provided is an external power supply too. Only use the power supply block provided with the appliance. Use of another mains block could damage your appliance and would not valid the guarantee.

4.4 Turning the appliance on and off

Press the button on the right side of the appliance:

The entry page appears on screen.

The message "Autotest: running" is shortly displayed, and then disappears.

Pressing this button turns the appliance off.



The ON/OFF button **lights up** when the appliance is working. Pressing the ON/OFF button for a long time **forces the shut-off** of the appliance; **pro-ceed this way only in case of necessity.**

5 Man-machine interface

5.1 Content of the screen

You can also select lines of tables.

7859 is an appliance with a capacitive touchscreen. No glove should be used. If you don't want to damage your screen, do not use any stylus or object.

You can recognize the « keys » by their dark grey frame, example the Home key:



The 7859 can work in RF or optical mode. You can switch from one mode to the other at start-up and from the homepage:



The Home page allows you to navigate among all functions of the appliance. You will find there the <u>LNB</u> – <u>DiSEqC</u> (in RF mode) and <u>Measures-TV-Spectrum</u> functions. But you will also find the <u>AUTOSET</u>, <u>Lists-,Library</u>, <u>Check Sat</u>, <u>Configuration</u>, <u>Constellation</u>, <u>Echo guard interval</u>, <u>optical power measurement</u> (in optical mode) <u>RF/Optical</u> and <u>Measurement map</u> keys.



RF mode

OPTICAL mode

On all pages is displayed the following information:







To navigate through a table inside a page or a window, a vertical slide appears with arrows to move up and down the table.

List	S				Pos B	VDC=12.8V IDC= 52mA	
List	:	HOT BIRD		HOT BIRD			Move up through the table
8	#	name	freq.	standard	config.		
0	93	N-TV HOT BIRD	10834 VL	DVB-S2 27500			Cursor to navigate up
0	94	SKY IT HOT BIRD	10853 HL	DVB-S 29900			or down
0	95	SNRT HOT BIRD	10873 VL	DVB-S 27500			
0	96	CYFRA+ HOT BIRD	10892 HL	DVB-S 27500			
0	97	ORANGE HOT BIRD	10911 VL	DVB-S2 27500			
0	98	NOVA HOT BIRD	10930 HL	DVB-S 27500			Move down
0	99	GLOBECAS HOT BIRD	10949 VL	DVB-S 27500			
0	100	RRSAT HOT BIRD	10971 HL	DVB-S2 29700			

To move faster, you can slide a cursor with your fingers.

5.2 Changing name or value

5.2.1 Changing inside a table

You can select a setup in the table. In this case, you can validate a setup by pressing the line you want to display.

In this example, you change from the TNT-R1 setup to the TNT-R4 in the Measure page:

wea	sures									IDC	= 0m	ia 🗖 🛨
<	ST ETIENNE	>	<	TNT-F	R1	>						
<	610.000 MHz	>	 	DVB-T/	н				.			
<	E38	>	ع (٦	8 MHz								
Cell	ID:0x3420 (1334	4)									-	
RF	51.1 dBμV	20	40		60		80		100		120	
C/N	31.2 dB	0	10		20		30		40		50	
BERi	6.8E-8	1E-1		1E-3		1E-5		1E-7		1E-9		~~~~`
BERG) < 2E-8	1E-1		1E-3		1E-5		1E-7		1E-9		<u> </u>
PER	< 2E-5	1E-1		1E-3		1E-5		1E-7		1E-9		
MER	33.8dB	15	20		25		30		35		40	
LKM	12.8dB	0	10		20		30		40		50	





5.2.2 Change with selection

When pressing a key, you may have a window with multiple choices. You only have to press the value you want to validate it, the key allows you to cancel and exit this window, like in the example below: In this example, the bandwidth changes from 8 to 6 MHz:



5.2.3 Change with virtual keyboard

If you want to enter a name of a number, a window appears with a numeric keypad and a virtual AZERTY keypad:



5.3 Lists of measurements and setup library

In order to make easier the recall of data on field, the appliance uses 20 measurement lists of each 50 lines and 1000 setups.

A setup corresponds to a terrestrial, cable or satellite emission.

A list of measurements corresponds to a particular installation: presence of several satellite dishes, of various switches...

Example of list (the background of the table is white)

Li	sts	5					VDC= 0 IDC= 0	.0V mA
Li	List :		ST ETI	ENNE		Library		
	õ	#	name	freq.	standard	config.		
	С	371	TNT-R1 ST-ETIENNE	E38	DVB-T/H 8M GI auto			
	С	372	TNT-R2 ST-ETIENNE	E44	DVB-T/H 8M GI auto			
	С	373	TNT-R3 ST-ETIENNE	E59	DVB-T/H 8M GI auto			
	С	374	TNT-R4 ST-ETIENNE	E40	DVB-T/H 8M GI auto			
	С	375	TNT-HD ST-ETIENNE	E49	DVB-T/H 8M GI auto			
	С	376	TNT-R6 ST-ETIENNE	E46	DVB-T/H 8M GI auto			
	С	377	FR INTER ST-ETIENNE	88.000	FM			
	С	378	EUROPE 1 ST-ETIENNE	104.800	FM		V	0

Libr	ary s	etups				
			ľ	Lists		
8	#	name	freq.	standard		
0	0	DIGITAL+ ASTRA 1	10729 VL	DVB-S2 22000		
0	1	ARD ASTRA 1	10743 HL	DVB-S 22000		
0	2	ANIXE HD ASTRA 1	10773 HL	DVB-S2 22000		
0	3	DIGITAL+ ASTRA 1	10788 VL	DVB-S 22000		
0	4	DIGITAL+ ASTRA 1	10817 VL	DVB-S2 22000		
0	5	HD+ ASTRA 1	10832 HL	DVB-S2 22000		
0	6	DIGITAL+ ASTRA 1	10847 VL	DVB-S 22000		
0	7	TVP HD ASTRA 1	10861 HL	DVB-S 22000	v	0

Example of library (the background of the table is yellow)

The same setup may be used in several measurement lists.

The same installation may use two satellite dishes

ASTRA 19.2 in DiSEqC position A

HOT BIRD 13 in DiSEqC position B

Another one may use three satellite dishes

ATLANTIC BIRD 3 in DiSEqC position A

ASTRA 1 in DiSEqC position B

HOT BIRD in DiSEqC position C

The same setup may be used several times in the same measurement list.

- ZDF SatCR slot 0
- ZDF SatCR slot 1
- ZDF SatCR slot 2
- ZDF SatCR slot 3...

If a parameter of a setup changes, for example a modification of rate or change from DVB-S to DVB-S2, only the setup inside the library should be updated.

A list of measurements is made of:

- a list name in 10 characters
- the lowest frequency of the LNB (OL1)
- the highest frequency of the LNB (OL2)
- the selection mode low band / high band of the LNB
- the selection mode of the polarization
- the presence of the position number of the positioner (motorized satellite dish)
- 50 lines including each:
 - a setup number corresponding to the setup list
 - the presence and the functioning mode of the switch, committed type
 - the position of the switch, committed type
 - the presence and the functioning mode of the switch, uncommitted type
 - the position of the switch, uncommitted type
 - the presence of SatCR equipment
 - the SatCR slot number
 - the position of the SatCR switch

A few of these parameters are specific to the waveband of the satellite and have no influence in terrestrial and cable modes.

A setup is made of:

- a setup name in 8 characters
- a place name in 10 characters
- a frequency
- a channel number in terrestrial or cable mode
- a frequency map in terrestrial or cable mode
- a vertical or horizontal polarization in satellite mode
- a low or high LNB band in satellite mode
- a standard
- an analogical mono stereo or NICAM mode in terrestrial or cable mode
- a constellation type 64QAM 256QAM under DVB-C
- a bandwidth 5, 6, 7 or 8 MHz under DVB-T and DVB-T2
- a symbol rate under DVB-C, DVB-S, DVB-S2 or DSS

According to the terrestrial, cable or satellite band mode and to the standard, some parameters have no influence.

The place name may distinguish two distinct emitters, example TF1 Fourvière and TF1 Chambéry.

Frequency and channel number are equivalent: a valid channel number has priority over a frequency.

The frequency map parameter associated with the setup allows frontiersmen to keep on using channel numbers.



Selecting a list in the **Lists** page automatically recalls all information associated with this list.



Selecting a **Setup** on a measurement page automatically recalls all information associated with this setup.

6 AUTOSET mode

ΠĘ

<u>Attention</u>: The Autoset channel research is only possible when at least one list is empty with enough place in the library

This mode allows an automatic research of setups and to provide information about the current place.

Autoset

You can access it through the key

on page Home.

The displayed lines on this page depend on the selected **Frequency band**. The key before the Mode line allows you to select between terrestrial, cable or satellite mode:



Once the mode selected, the keys of the various parameters activate or deactivate each option.

A green check shows that the parameter is included in the research. If there is no green check, the parameter will not be taken into account for the research.



6.1 Terrestrial mode

This mode allows automatic research on the terrestrial frequency band.

The table allows the selection of:

- Standards
- Channel widths
- The channel range of the research (i.e. 21 to 60).

The goal is to make researches shorter by defining at best the settings (example: in France, no DVB-T2, band width DDT 8MHz first channel 21, last channel 60)

Autoset	IDC= 0mA
Mode: Terrestrial Frequency map France	
DVB-T DVB-T2 1.7 5 MHz 6 MHz 7 MHz channel: E21 to channel: E60	8 MHz
Start	

6.2 Satellite mode

This mode allows automatic research on the satellite frequency band.

The table allows the selection of:

- LNB bands
- LNB polarizations.

The goal is to make researches shorter again

Autoset	
Vertical High	
Start	

6.3 Cable Mode

This mode allows automatic research on the **cable** frequency band.

The table allows the selection of:

- Standards
- Channel widths
- The search range of channels



6.4 «START » menu key

No matter which mode is selected, press the "**START**" key when the table is filled to launch the research. Pressing "**Stop**" will abort the research.

When the research is done or if the user aborted it, the appliance turns automatically to the **Measurement map** function.

Measur	Measurement map VDC= 0.00 IDC= 0m														
A	JTOSET					2/6									
freq.	std	RF	C/N	BERi	BERo	PER	MER								
E38	DVB-T/H	51.0	31.1	4.7E-8	<1E-8	<1E-5	33.7								
E40	DVB-T/H	0.0	> 0.0												
E44	DVB-T/H	0.0	> 0.0												
E46	DVB-T/H	0.0	> 0.0												
E49	DVB-T/H	0.0	> 0.0												
E59	DVB-T/H	0.0	> 0.0												
								V							

Any detected channel will be registered into the first empty list (automatically renamed AUTOSET) **and** into the fist available setups of the library, starting from the end of the table.

Lists					VDC=12.8V IDC= 52mA		Lists	í		Linte			VDC=12 IDC= 52	.6V mA
List :	AUTOS	ET		Library			List :		5	ASTRA 2	<u>í</u>	rary		
8 #	name	freq.	Nandard	config.			<u>``</u> #	name	6	TURKSAT	Ĩ	ontig.		
380	C0 Autoset	E38 DVI	3-T/N 8M GI				0 380	C0 Autoset	7	AST1 SATCR	<u> </u>		\land	a m
0 381	C1	E40 DVI	3-T/H 8M OL				381	C1 Autoset	8		<u> </u>			
0 200	Autoset C2	E44 DVI	auto 3-T/H 8M GI				0 382	C2						
0 302	Autoset	E44	auto B-T/H 8M GL				0 222	C3	9	AST+ST-ET	<u> </u>	┛┟	-	
383	Autoset	E46	auto	\			0 303	Autoset C4	10	AUTOSET	é			
384	C4 Autoset	E49	3-T/H 8M GI auto	X			384	Autoset	11		Ĩ			
385	C5 Autoset	E59 DVI	3-T/H 8M GI				385	Autoset	12		₩ W			
	Autoset		uuto	$\overline{}$			0			1 2-1				
				`			0				<u> </u>		\checkmark	0
							·(1				
Library	setups				VDC= 0.0V				Th	ne new list	is cre	ated ir	h the f	irst
				Lists		\mathbf{i}		`	av	ailable lis	t			
<u>3</u> #	name	freq.	5	standard										
0 379	ST-ETIENNE	97.100	0	FM					ть			~ f th ~		int in
0 38	C0 Autoset	E38	DVB-T	7/H 8M GI auto			\mathbf{i}				name	or the	new	ISUS
O 38 [.]	C1	E40	DVB-T	/H 8M GI auto	_			、 、	AU	JIOSEI				
- 39	C2	E44	DVR-T	/H SM CLauto				\mathbf{i}						
	Autoset		010-1											
38:	Autoset	E46	DVB-1	/H 8M GI auto				\sim	Ne	ew found o	channe	els are	adde	ed one
384	Autoset	E49	DVB-1	7H 8M GI auto					by	one into	the ne	w list		
0 38	C5 Autoset	E59	DVB-1	7/H 8M GI auto										
38	•						$\overline{}$							
									Ne by of of	ew found of one into the library the table	channe the firs /, starti	els are t avail ing fro	adde able : m the	ed one setups e end

7 Measurement lists

7.1 The list page

In this page, you can select the list where you will work on measurements.

Pressing the Lists-Library key

gives you access to the **LISTS** function:

List	S						
List :		AST	RA 1		Library		
3	#	name	freq.	standard	config.		
0	0	DIGITAL+ ASTRA 1	10729 VL	DVB-S2 22000			
0	1	ARD ASTRA 1	10743 HL	DVB-S 22000			
0	2	ANIXE HD ASTRA 1	10773 HL	DVB-S2 22000			
0	3	DIGITAL+ ASTRA 1	10788 VL	DVB-S 22000			
\circ	4	DIGITAL+ ASTRA 1	10817 VL	DVB-S2 22000			
\circ	5	HD+ ASTRA 1	10832 HL	DVB-S2 22000			
\circ	6	DIGITAL+ ASTRA 1	10847 VL	DVB-S 22000			
0	7	TVP HD ASTRA 1	10861 HL	DVB-S 22000		V	0

Lists are ranked from 0 to 19. To select the one you want, press the following key. Lists are displayed. Press the one you want:

List	s					VDC= 0 IDC= 0	nA math		
List :		ASTI	0	ASTRA 1	Ĩ		rary		
8	#	name	1	HOT BIRD	圓		ontig.		
$ \circ$	0	DIGITAL+ ASTRA 1	2	ASTRA1+HOT	Ĩ		***		
0	1	ARD ASTRA 1	3	ATLANTIC			***		
0	2	ANIXE HD ASTRA 1	4	ASTRA 3			***		
\circ	3	DIGITAL+ ASTRA 1	5	ASTRA 2					
0	4	DIGITAL+ ASTRA 1	6	TURKSAT			~~-		
0	5	HD+ ASTRA 1	7	AST1 SATCR					
0	6	DIGITAL+	Ľ						
0	7	TVP HD ASTRA 1			J	1			0

In this example, we selected ST ETIENNE.

List	S	ſ		11-4-)	VDC=12 IDC= 52	nev Ma		List	S					
List	:	ASTF	6	TURKSAT	Ĩ		rary				List	:	ST ETI	ENNE		Library	
8	ŧ	name	7	AST1 SATCR	劃		ontig.				3	#	name	freq.	standard	config.	
0	0	DIGITAL+ ASTRA 1	8	ST ETIENNE	Ĩ		****				\circ						
0	1	ARD ASTRA 1	9	AST+ST-ET	Ĩ		***				0	371	TNT-R1 ST-ETIENNE	E38	DVB-T/H 8M GI auto		
0	2	ANIXE HD ASTRA 1	10	AUTOSET			~~~			-	0	372	TNT-R2 ST-ETIENNE	E44	DVB-T/H 8M GI auto		
0	3	DIGITAL+ ASTRA 1	11								0	373	TNT-R3 ST-ETIENNE	E59	DVB-T/H 8M GI auto		
0	4	DIGITAL+ ASTRA 1	12				***				0	374	TNT-R4 ST-ETIENNE	E40	DVB-T/H 8M GI auto		
0	5	HD+ ASTRA 1	13			~	***				0	375	TNT-HD ST-ETIENNE	E4 9	DVB-T/H 8M GI auto		
0	6	DIGITAL+ ASTRA 1					w.e.w				0	376	TNT-R6 ST-ETIENNE	E46	DVB-T/H 8M GI auto		
$\left[\circ \right]$	7	TVP HD ASTRA 1			J	1	J		0		0	377	FR INTER ST-ETIENNE	88.000	FM		0


Attention: A list may contain a Satellite and a Terrestrial setup.

7.2 Modification of a list

To change the name of the list of ST ETIENNE, you must push on its name, then on the symbol of the keypad. A virtual keypad shows up. Type the new name (SEFRAM in our example).

List	s						
List	:	ST ETI	ENNE		Library		
8	#	name	freq.	standard	config.		
0							
$^{\circ}$	371	TNT-R1 ST-ETIENNE	E38	DVB-T/H 8M GI auto			
$^{\circ}$	372	TNT-R2 ST-ETIENNE	E44	DVB-T/H 8M GI auto			
$^{\circ}$	373	TNT-R3 ST-ETIENNE	E59	DVB-T/H 8M GI auto			
0	374	TNT-R4 ST-ETIENNE	E40	DVB-T/H 8M GI auto			
0	375	TNT-HD ST-ETIENNE	E49	DVB-T/H 8M GI auto			
$^{\circ}$	376	TNT-R6 ST-ETIENNE	E46	DVB-T/H 8M GI auto			
$^{\circ}$	377	FR INTER ST-ETIENNE	88.000	FM		V	0





To add a setup to the list, select the line. A window shows up:

st	s								Lis	Lists	Lists	Lists	Lists	Lists	Lists 800=12	Lists V0C-12 0 00C- 52m	Lists 000-12.00	Lists VOC-12.8V IOC-52mA	Lists VIC-12 6V IDC- 52mA	Lists VIC-12 6V	Lists VIC-12.6V
st	:	ST ETI	ENNE		Library				Lis	List :	List : ST ETI	List : ST ETIENNE	List : ST ETIENNE	List ST ETIENNE	List : ST ETIENNE Library	List : ST ETIENNE Library	List : ST ETIENNE Library	List : ST ETIENNE Library	List : ST ETIENNE Library	List : ST ETIENNE Library	List : ST ETIENNE Library
(jo	#	name	freq.	standard	config.				0	5	6	Č.	List modification	Contraction Callor	Contraction Callon	List modification	Elst hlodification	List filodification	List modification	List modification	
0							-		0	Se	Setup	Setup	Setup	Setup	Setup	Setup	Setup	Setup	Setup	Setup	Setup
0	371	TNT-R1 ST-ETIENNE	E38	DVB-T/H 8M GI auto					0	0	0	0									
\circ	372	TNT-R2 ST-ETIENNE	E44	DVB-T/H 8M GI auto				\rightarrow													
0	373	TNT-R3 ST-ETIENNE	E59	DVB-T/H 8M GI auto							<u> </u>									<u> </u>	
0	374	TNT-R4 ST-ETIENNE	E40	DVB-T/H 8M GI auto								0									
0	375	TNT-HD ST-ETIENNE	E49	DVB-T/H 8M GI auto								0									
\circ	376	TNT-R6 ST-ETIENNE	E46	DVB-T/H 8M GI auto						0 370	ST-ETIENNE BTT FR INTER	ST-ETIENNE E40	ST-ETIENNE E40 auto	G ATT FR INTER R 000 FM	O 375 ST-ETIENNE C40 auto	C 370 ST-ETIENNE E40 auto	ATT FRINTER 25 000 FM	O 376 ST-ETIENNE C40 auto	C 370 ST-ETIENNE E40 auto	ATT FR INTER 19 000 FM	ST-ETIENNE E40 auto
0	377	FR INTER ST-ETIENNE	88.000	FM		V	3				ST-ETIENNE	ST-ETIENNE 66.000	ST ST-ETIENNE 66.000 FM	ST-ETIENNE GO.000 FM	S1/ ST-ETIENNE 00.000 PM	ST/1 ST-ETIENNE 00.000 PM	ST-ETIENNE 00.000 FM	ST-ETIENNE GO.000 PM	S1/1 ST-ETIENNE 00.000 PM		S7/1 ST-ETIENNE 00.000 PW

Attention: If the line contains a setup, it shall be erased. To cancel, press:

By pressing the key before Setup, you disclose the available setups from the library (you cannot create a setup from a list; to create a setup, see <u>Setup creation or modification in the library</u>):

แระ	s						in and
List	:	ST ETI					
8			List	modificatio	1		
0	Set	up					
0	Ĩ		_				1
0	I						
\bigcirc							
0							
0							
	376	ST-ETIENNE	E46	auto			
\circ	377	FR INTER ST-ETIENNE	88.000	FM		~	0



Scroll the list up or down to find the setup you want to add to your list. Press the line you want:

List	S	_	Librar	y setups	VGC= 0.8V IDC= 0mA		Lists		Librar	v setups	VDC. 8.8V IDC- 0mA
List	: sı	373	TNT-R3	ST-ETIENNE		p. 37	List :	S1 373	TNT-R3	ST-ETIENNE	
6	r	374	TNT-R4	ST-ETIENNE			<u> </u>		List mo	dification	
0	Setup	375	TNT-HD	ST-ETIENNE			Setu	p		#380 C0 (Autoset)	
0	(Committed) \$	376	TNT-R6	ST-ETIENNE			0				
		977		OT ETIENNE							

The setup is now in the list:

List	ts					
List	::	ST ETI	ENNE		Library	
8	#	name	freq.	standard	config.	
0	380	C0 Autoset	E38	DVB-T/H 8M GI auto		
0	371	TNT-R1 ST-ETIENNE	E38	DVB-1/H 8M GI auto		
0	372	TNT-R2 ST-ETIENNE	E44	DVB-T/H 8M GI auto		
0	373	TNT-R3 ST-ETIENNE	E59	DVB-T/H 8M GI auto		
0	374	TNT-R4 ST-ETIENNE	E40	DVB-T/H 8M GI auto		
0	375	TNT-HD ST-ETIENNE	E49	DVB-T/H 8M GI auto		
0	376	TNT-R6 ST-ETIENNE	E46	DVB-T/H 8M GI auto		
0	377	FR INTER ST-ETIENNE	88.000	FM		0

You may erase the setup from the list by pressing the check to the left of the setup or to the setups you have to delete. Then click the basket and select the deletion of the selected setup:

Lis	ts						Lis	ts					VIDC= 0.8V IDC= 0mA
Lis	t:	ST ETI	ENNE		Library		Lis	::		TIENNE		Library	
0	#	name	freq.	standard	config.		8	#	name	freq.	standard	config.	
C	380	C0 Autoset	E38	DVB-T/H 8M GI auto			0	380	C0 Autoset		Delete		
C	371	TNT-R1 ST-ETIENNE	E38	DVB-T/H 8M GI auto			0	371	TNT-R1 ST-ETIENNE	Sele	cted items		
C	372	TNT-R2 ST-ETIENNE	E44	DVB-T/H 8M GI auto				372	TNT-R2 ST-ETIENNE				
C	373	TNT-R3 ST-ETIENNE	E59	DVB-T/H 8M GI auto			\circ	373	TNT-R3 ST-ETIENNE				
C	374	TNT-R4 ST-ETIENNE	E40	DVB-T/H 8M GI auto				374	TNT-R4 ST-ETIENNE				
C	375	TNT-HD ST-ETIENNE	E49	DVB-T/H 8M GI auto				375	TNT-HD ST-ETIENNE	E49	DVB-T/H 8M GI auto	wa w	
C	376	TNT-R6 ST-ETIENNE	E46	DVB-T/H 8M GI auto				376	TNT-R6 ST-ETIENNE	E46	DVB-T/H 8M GI auto		
C	377	FR INTER ST-ETIENNE	88.000	FM		V 0		377	FR INTER ST-ETIENNE	88.000	FM	***	

LISI	S						
List	:	ST ETI	ENNE		Library		
8	#	name	freq.	standard	config.		
0						\land	
0	371	TNT-R1 ST-ETIENNE	E38	DVB-T/H 8M GI auto			
0	372	TNT-R2 ST-ETIENNE	E44	DVB-T/H 8M GI auto			
0	373	TNT-R3 ST-ETIENNE	E59	DVB-T/H 8M GI auto			
0	374	TNT-R4 ST-ETIENNE	E40	DVB-T/H 8M GI auto			
0	375	TNT-HD ST-ETIENNE	E49	DVB-T/H 8M GI auto			
0	376	TNT-R6 ST-ETIENNE	E46	DVB-T/H 8M GI auto			
0	377	FR INTER ST-ETIENNE	88.000	FM		V	0

You can also delete the totality of a list by pressing directly on the basket then by selecting

- 7859 -

In a satellite setup, you can change the switch, the Uncommitted Port and the DCSS by activating any of these keys (this change will affect only the setup in this list, not in the library):



Library

8 Setup library

8.1 The library page

Pressing the Lists-Library key

page, you have access to the Library by pressing

gives you access to the LISTS function. From this

Libr	ary s	etups			IDC= 0	mA = +
				Lists		
6	#	name	freq.	standard		
0	379	FR MUSIQ ST-ETIENNE	97.100	FM		
0	380	C0 Autoset	E38	DVB-T/H 8M GI auto		
0	381	C1 Autoset	E40	DVB-T/H 8M GI auto		
0	382	C2 Autoset	E44	DVB-T/H 8M GI auto		
0	383	C3 Autoset	E46	DVB-T/H 8M GI auto		
0	384	C4 Autoset	E49	DVB-T/H 8M GI auto		
0	385	C5 Autoset	E59	DVB-T/H 8M GI auto		
0	386				V	

8.2 Creation or modification of setups in the library

To create or change a setup in the library, you have to select a line in the table. A window pops up:



Lib	rary s	etups			VDC= 0.0V IDC= 0mA			Libra	ry setups		VBC= 0.	A A
			ſ	Lists						Setup modificatio	n	
	#	name	freq	standard						3	70	
C	368							Ō	36 Satellite	· · · · · · · · · · · · · · · · · · ·		5
С	369							0	³⁶ Frequency	10729 MHz	1	
С	370						\rightarrow	\circ	37 Standard			
С	371	ST-ETIENNE	E38	DVB-T/H 8M GI auto				\circ	37	DVB-32		
С	372	TNT-R2 ST-ETIENNE	E44	DVB-T/H 8M GI auto				\circ	37 Polar./Band	Low	Vertical	
С	373	TNT-R3 ST-ETIENNE	E59	DVB-T/H 8M GI auto				\circ	37 Symbol rate	22000 kBd		
С	374	TNT-R4 ST-ETIENNE	E40	DVB-T/H 8M GI auto		-		0	37		·	
C	375	TNT-HD ST-ETIENNE	E49	DVB-T/H 8M GI auto		0		0	37ST-ETIENNE			

- 7859 -

You may erase the setup from the list by pressing the check to the left of the setup or to the setups you have to delete. Then click the basket and select the deletion of the selected setup:

From this window, you can create a terrestrial, satellite KU, L or C setup. To proceed, see chapter 5 <u>Man-machine interfaces</u>

Terrestrial setup:



Under standard DVB-T/H DVB-T2

In terrestrial analogical standard (L, BG, DK, I and MN)

0



37

> <u>Setup Satellite KU, L or C</u>:

Ku L or C corresponds to the selected band



9 Check Sat



to access the Check Sat mode.



The appliance has 32 possible orbital positions for satellites. It is provided with near of 10 satellites registered.

4 transponders are appended to each satellite.

You can select the satellite by pressing « Name and position of the satellite ».

To modify a transponder, you must press the corresponding key:



9.1 Updating satellites

You can update frequencies of the checks sat by consulting the file PDF posted on-line on the site web of SEFRAM. . <u>http://www.sefram.com/telechargement/fichier-de-configuration.html</u>

You have to modify frequencies, following the previous paragraph and using the file updated monthly on the web site of SEFRAM.

We advise you to check and to update your frequencies every three months. We advise you to check and to update your frequencies every three months

9.2 Check Sat function

Procedure:

1/ Connect the satellite dish to the appliance and start it up.



2/ Validate the remote power supply:

- VDC lights up.
- Check the power supply current of the LNB (IDC at the top right corner of the screen should be between 50 and 200mA).

See chapter Remote power supply / LNB - DiSEqC

3/ On the Home page, go to the Check Sat mode.

Select the satellite to aim at in the list (example ASTRA1)



4/ Slowly orientate the satellite dish until hearing the locking melody and getting the best quality.

5/ Slightly turn the LNB to get the best quality (counter-polarization).

You will hear a melody as soon as a first transponder is detected; then, you will hear beeps. These beeps are closer and closer as the quality increases.





If the appliance is not synchronized on all four transponders, the quality indication is red.

If the appliance is synchronized on all four transponders but the reception quality is average, the quality indication is **orange**.









9.3 Checking the aligned satellite

To check if you have aimed the right satellite, press the NIT key.

The appliance searches the MPEG NIT table on one of the 4 transponders and displays the name of the satellite:



Attention: The displayed name depends on the content of the MPEG NIT table. Some distributors provide no (or poor) such table. The displayed information may be wrong.

9.4 Double Check Sat

US

This mode allows you to orientate a double LNB by checking 4 transponders on 2 selected satellites. This mode is identical to the simple Check Sat mode.

To access the double Check Sat mode, you have to trigger the Double key.



9.4.1 Recall

Azimuth

Position of the satellite dish on the horizontal plane with reference to the north. Measured in degrees.



Elevation

Tilt angle under which the beam from the satellite reaches your antenna. Measured in degrees using what is specified on the stand of the satellite dish.



Polarization

Rotation required for the LNB from a vertical line. Measured in degrees.



10 TERRESTRIAL check

To access to the menu terrestrial check from Home page, press The following page appears:



Set up your check:





i

p. 48

🏯 Antenna pointing

i



Enter 4 frequencies or channels of the transmitter you try to check.

http://www.sefram.com/telechargement/fichier-de-configuration.html

Once you informed the 4 transponders, slowly orientate the satellite dish until hearing the locking melody and getting the best quality.





Press key permits to list the services distributed on the multiplex:



11 The Measures-TV-Spectrum page



12 Measures (MEASURES-TV-SPECTRUM)

Pressing the MEASURE zone gives access to the **MEASURES** function.

In this page, you can either perform measurements on a memorized program in the current list (see chapter « <u>Measurement list</u> »), or change parameters manually, or use the AutoLock function

12.1 Autolock function

This function is design to lock on a digital signal (terrestrial, cable or satellite)

You just have to enter the frequency or the channel (for terrestrial), then press AutoLock, The instrument will find automatically in few seconds the digital standard, the modulation type and all other parameters of the signal.

Example for terrestrial, channel 38 (frequency 610MHz):



Example for satellite low vertical polarization, frequency 12109 MHz :

Measures									
ASTR.	A 1	> <		Setu	ıp	>			
🦿 12109 I	MHz	> (), D	VB-S	2				
27500	٨Bd								
Horizoi	ntal		R H	ligh					
	20	-	40		60		80	100	120
C/N	0		10		20		30	40	50
BERi	Ē	1E-1		1E-3		1E-5	1E-	7	1E-9
BERo		1E-1		1E-3		1E-5	1E-	7	1E-9
PER		1E-1		1E-3		1E-5	1E-	7	1E-9
MER	0		5		10	•	15	20	25
LKM	0		10		20		30	40	50

12.2 Modification of parameters

	Mea	sures										VD(IDC	C= 0.0 = 0m	V - t
	<	ST ETIENNE	۶			Setu	р	>						
		658.186 MHz	>		÷ [оvв-т	/H							
	\triangleleft	E44	>		٦ (8 MHz								
1	Cell	ID:0x0003 (3)												
	RF	49.1 dBµV	20		40		60		80		100		120	
	C/N	27.2 dB	0		10		20		30		40		50	
	BERi	2.2E-5	1	E-1		1E-3		1E-5		1E-7		1E-9		$\langle q \rangle$
	BERo	< 5E-8	1	E-1		1E-3		1E-5		1E-7		1E-9		``
	PER	< 5E-5	1	E-1		1E-3		1E-5		1E-7		1E-9		
	MER	33.0dB	15		20		25		30		35		40	
	LKM	12.0dB	0		10		20		30		40		50	

The various parameters are:

- The name of the setup (selection on the active list)
- The frequency of the emitter or transponder (and the true frequency of satellite)
- The standard and bandwidth for DVB-T/H and DVB-T2
- The corresponding channel number for terrestrial and cable mode
- The symbol rate for the satellite
- The polarization and the band for the satellite
- The audio mode for the analogical TV

You can shift from terrestrial to satellite mode by:

- Changing the setup frequency
- Changing of standard
 - Changing of setup (from a terrestrial to a satellite setup)

12.3 Level measurements

_

ίβ,

You can measure levels at a specific frequency with a detection matching the standard.

	In terrestrial band, for an user socket, the level should be:
	- between 50 and 66 dBµV under FM
115	 between 35 and 70 dBµV under DVB-T/H, DVB-T2
	- between 57 and 74 dB μ V in any other case
لله الله	In satellite band, for an user socket, the level should be: - between 47 and 77 dBµV.

Example in terrestrial mode:



The appliance makes different measurements according to the current standard.

The other possible measurements are:

- Average measurement
- Peak measurement
- Power measurement.



The best is to be the closest possible of the green bar without exceeding it. For the MER measure, the value must be superior to the mini threshold.

12.4 Satellite band

The following table sums up the measurement types and the frequencies of the audio carrier waves for each standard:

Standard	Video carrier	Measure
PAL	FM	Peak
SECAM	FM	Peak
NTSC	FM	Peak
DVB-S	Digital	Power
DSS	Digital	Power
DVB-S2	Digital	Power

12.5 Terrestrial band

The appliance automatically makes level measurements on the Video carrier wave.

The following table sums up the measurement types and the frequencies of the audio carrier waves for each standard:

Standard	Video carrier	Measure	Sound carrier				
			Mono	stereo	NICAM		
BG	negative, AM	peak	FM	FM	DQPSK		
			5.5 MHz	5.74 MHz	5.85 MHz		
DK	negative, AM	peak	FM	FM	DQPSK		
			6.5 MHz	6.258 MHz	5.85 MHz		
I	positive, AM	peak	FM		DQPSK		
			6.0 MHz		6.552 MHz		
L	positive, AM	peak	AM		DQPSK		
			6.5 MHz		5.85 MHz		
MN	negative, AM	peak	FM	FM			
			4.5 MHz	4.72 MHz			
DVB-C	digital	power					
DVB-T/H	digital	power					
DVB-T2	digital	power					
DAB/DAB+	digital	power					
FM	FM	average					
Carrier	not modulated	average					

The appliance displays the level of the $\ensuremath{\textit{Video}}$ carrier wave and the $\ensuremath{\textit{C/N}}$ ratio.

12.6 Thresholds

Predefined thresholds are used to assess if the measurement is pertinent.

Standard	Min	Max
Terrestrial analog TV	57	74
DVB-C/C2	57	74
DVB-T/T2	35	70
DAB-DAB+	35	70
FM, Carrier	50	66
Satellite analog TV	47	77
DVB-S, DSS	47	77
DVB-S2	47	77



12.7 Digital measurements

In digital measurement mode, in addition to the **RF** level and to the **C/N** here above, the appliance also displays the various **BER** (Bit Error Rate), the **PER** (Packet Error Rate) and the **MER** (Modulation Error Ratio) under **DVB-T/T2/T2Lite**, **DVB-C/C2**, **DVB-S/S2** or **DSS**.

You also get the LKM:x.xdB (Link Margin) specification.

This expression in dB is the difference between the measured MER and the limit MER before disconnection of the image: **it's the security available before disconnection**.



"Sync ?" displayed on screen means that the signal is absent or unlocked; check its presence, the modulation parameters, the presence of remote power supply and the LNB and DiSEqC parameters under satellite band.



The sign < before a value or error rate shows that there is no error but that 10^{-X} bits have been tested (i.e. < 10^{-8} means that 10^{8} bits have been tested).

IL.	 You can shift from terrestrial to satellite mode by: Changing the setup frequency Changing of standard Changing of setup (from a terrestrial to a satellite setup)
-----	---

12.8 DVB-T/H

	₩ ⇔ TUNER⇔ DE			REED SOLOMON	DECODA MPEG ♠ ER	GE d	
Mea	sures					VDC= IDC=	0.0V OmA
	ST ETIENNE	> <	Setup	>			
	658.186 MHz	> *	DVB-T/H				
	E44		8 MHz				
Cell	ID:0x0003 (3)						•
RF	49.1 dBμV	20 40	60	80	1	00 12	:0
C/N	27.2 dB	0 10	20	30		40 £	10
BERi	2.2E-5	1E-1	1E-3	1E-5	1E-7	1E-9] 4
BERo	o < 5E-8	1E-1	1E-3	1E-5	1E-7	1E-9	
PER	< 5E-5	1E-1	1E-3	1E-5	1E-7	1E-9	
MER	33.0dB	15 20	25	30	3	35 4	0
LKM	12.0dB	0 10	20	30		40 5	0

Display of the measures of:

- BERi: error rate before Viterbi
- BERo: error rate after Viterbi
- PER: error rate after Reed Solomon (error rate packet)
- MER: modulation error rate
- LKM: noise margin (Link Margin)

BERx: 'bits' error rate

Ratio between the number of false bits / number of transmitted bits during the measurement time

PER: 'packets' error rate

Ratio between the number of false packets / number of transmitted packets during the measurement time Recall: Under DVB-T/H, a packet is made of 204 octets; a packet is "false" if it includes more than 8 wrong octets (correction by Reed Solomon coding).

Display of the value of Cell ID from the diffuser and specific to the emitter.

12.9 DVB-T2 /T2 Lite



Display of the measures of:

- **BERi**: error rate before LDPC
- BERo: error rate after LDPC
- **PER**: error rate after BCH (lost packets)
- MER: modulation error rate
- LKM: noise margin (Link Margin)

Recall:

LDPC: Low Density Parity Check

BCH: Bose Chauhuri Houquenohem

The concatenation Viterbi + Reed Solomon of the correction of DVB-T/H has been replaced by the concatenation LDPC + BCH under DVB-T2.

Display of the values of Cell_ID from the diffuser and specific to the emitter.

12.10 DVB-C



Display of the measures of:

- BERo: error rate before Reed Solomon
- **PER**: error rate after Reed Solomon (error rate packet)
- MER: modulation error rate
- LKM: Noise margin (Link Margin)

BERo: error rate 'bits'

Ratio between the number of false bits / number of transmitted bits during the measurement time

PER: error rate 'packets'

Ratio between the number of false packets / number of transmitted packets during the measurement time

Recall: Under DVB-C, a packet is made of 204 bites; a packet is "false" if it includes more than 8 wrong octets (correction by Reed Solomon coding).

12.11 DVB-C2



Display of the measures of:

- **BERi**: error rate before LDPC
- BERo: error rate after LDPC
- **PER**: error rate after BCH (lost packets)
- MER: modulation error rate
- LKM: noise margin (Link Margin)

Recall:

LDPC: Low Density Parity Check

BCH: Bose Chauhuri Houquenohem

• Active PLP and Data slice

12.12 DVB-S et DSS



Display of the measures of:

- BERi : error rate before Viterbi
- BERo : error rate after Viterbi
- **PER** : error rate after Reed Solomon (error rate packet)
- MER : modulation error rate
- LKM : Noise margin (Link Margin)
- BERx : error rate 'bits'

Ratio between the number of false bits / number of transmitted bits during the measurement time

PER : error rate 'packets'

Ratio between the number of false packets / number of transmitted packets during the measurement time

Recall: Under QPSK (DVB-S) a packet is made of 204 octets; a packet is "false" if it includes more than 8 wrong octets (correction by Reed Solomon coding). Under DSS, a packet is made of 146 octets.

12.13 DVB-S2



Meas	ures									VDC=12. IDC= 49r	8V nA = +
	ASTRA 1			DIGIT	AL+	>					
	10729 MHz		ا ج	DVB-S	2				<u> </u>		
	22000 kBd									T	
	Vertical		5	Low				:		;	
RF	47.9 dBμV <mark>20</mark>		40		60		80		100	120	
C/N	15.5 dB <mark>o</mark>		10		20		30		40	50	
BERi	4.0E-3	1E-1		1E-3		1E-5		1E-7		1E-9	(()
BERo	< 9E-9	1E-1		1E-3		1E-5		1E-7		1E-9	<u> </u>
PER	< 1E-5	1E-1		1E-3		1E-5		1E-7		1E-9	
MER	14.0dB <mark>0</mark>		5		10		15		20	25	
LKM	7.1dB <mark>0</mark>		10		20		30		40	50	

Display of the measures of:

- BERi : error rate before LDPC
- BERo : error rate after LDPC
- **PER** : error rate after BCH (lost packets)
- MER : modulation error rate
- LKM : Noise margin (Link Margin)

Recall:

LDPC: Low Density Parity Check

BCH: Bose Chauhuri Houquenohem

The concatenation Viterbi + Reed Solomon of the correction of DVB-S has been replaced by the concatenation LDPC + BCH under DVB-S2.

13 Spectrum analyzer

Pressing SPECTRUM gives access to the **SPECTRUM ANALYSER function.** (graphical representation frequency / amplitude of the present signals in the input of the device)



2 predefined bandwidths are available: terrestrial and satellite. To swap from satellite to terrestrial, press the key, as shown on the bottom side of the screen.

The input attenuator is automatically tuned according to the level of the signals measured.

Filters are automatically selected according to the « Span ».

The filter used is displayed on the upper left corner.

Parameters of the spectrum are:



14 Image and Sound

Pressing the TV zone gives access to the **TV** function.

14.1 Digital TV

The name of the service and its main characteristics are displayed on top left of the screen.

- 720x576i: picture resolution 720 pixels / line, 576 lines, interlace
- 25 Hz: frame frequency
- MPEG-2: picture compression
- Video Rate 4.106 Mbits/s : instantaneous binary rate of the service
- Audio MPEG Layer II: sound compression

On this page, there are 3 keys at the bottom of the screen; they will be described in the next chapters



14.2 Full screen mode

Pressing the key displays the image in full screen; only remain the battery level and the intensity + voltage of the remote power supply:



To exit, you only have to touch the screen anywhere.

14.3 Audio

an adjustment bar shows up: To set the volume, press

The instrument can decode the following digital sound formats:

MPEG-1 L	MPEG-1 L1/L2							
AAC	Advanced Audio Coding	License Via Licensing						
HE-AAC	High Efficiency AAC	License Via Licensing						
Dolby Digit	al	License Dolby®						
Dolby Digit	al Plus	License Dolby [®]						

Made under license by Dolby laboratories.

Dolby and the double-D symbol are trademarks of Dolby Laboratories

Table of services 14.4

Pressing gives access to the list of services:

Service list								
	Service	Provider	SID	LCN	Α	Туре		
	D8	NTN	513	8		Digital TV		
	BFM TV	NTN	515	15		Digital TV		
	i>TELE	NTN	516	16		Digital TV		
	D17	NTN	517	17		Digital TV		
	Gulli	NTN	518	18		Digital TV		
	France 4	NTN	519	14		Digital TV		
			 					

This function allows selecting the channel you want to display. You only have to press the line you want.

15 Remote power supply / LNB – DiSEqC

The LNB-DiSEqC

key gives you access to the remote power supply / LNB-DiSEqC.

To start the remote power supply, press the key after Remote supply:



15.1 Terrestrial band

In terrestrial mode, you can select:



A green check shows which voltage is selected.

15.2 Satellite band

15.2.1 Power ON

Setting the remote power supply to satellite:



See chapter <u>Man-machine interface</u> for any change.

15.2.1 Switches

2-satellite switch

- * 22 kHz
- * ToneBurst (MiniDiSEqC)
- *DiSEqC Committed or Uncommitted

4-satellite switch

* DiSEqC Committed or Uncommitted



16-satellites switch

* DiSEqC Committed + Uncommitted

	Switch line		Uncommitted line	
Satellite	Position	DiSEqC command	Position	DiSEqC command
1	Pos A	Option A + Position A	Pos 1	Input 1
2	Pos B	Option A + Position B	Pos 1	Input 1
3	Pos C	Option B + Position A	Pos 1	Input 1
4	Pos D	Option B + Position B	Pos 1	Input 1
5	Pos A	Option A + Position A	Pos 2	Input 2
6	Pos B	Option A + Position B	Pos 2	Input 2
7	Pos C	Option B + Position A	Pos 2	Input 2
8	Pos D	Option B + Position B	Pos 2	Input 2
9	Pos A	Option A + Position A	Pos 3	Input 3
10	Pos B	Option A + Position B	Pos 3	Input 3
11	Pos C	Option B + Position A	Pos 3	Input 3
12	Pos D	Option B + Position B	Pos 3	Input 3
13	Pos A	Option A + Position A	Pos 4	Input 4
14	Pos B	Option A + Position B	Pos 4	Input 4
15	Pos C	Option B + Position A	Pos 4	Input 4
16	Pos D	Option B + Position B	Pos 4	Input 4

15.2.1 Positioner



The appliance sends a DiSEqC command that triggers the rotation of a motorized satellite dish.

In this example, the position is 2 (1 to 127 pre-loaded positions in the positioner)

If the positioner is on No, it is deactivated

See chapter <u>Man-machine interface</u> for any change.

15.2.2 DCSS

Description:

DCSS Digital Channel Stacking system: signal distribution system using frequency transposition.

Used in satellite distribution for multiple or single dwelling, with several set top boxes.

To give several receptors access to the whole spectrum and all polarizations, you need **one coaxial cable per receptor** and a suitable installation (multiple LNB, Quattro and multi-switches).

The DCSS system allow to feed dwellings with one or more satellites using only one coaxial cable (SCD=SIN-GLE CABLE DISTRIBUTION).





The DCSS is an extension of the DiSEqC protocol that allows the connection of several receptors on **only one coaxial cable**, no matter the band (H/L) and the polarization (H/V).

Functioning:

Each satellite receptor uses a fix frequency band (Slot or Port), whose width is (more or less) equal to the width of the transponder.

The receptor requires a specific transponder frequency (frequency Ku) via a DiSEqC command.

Some equipment on the satellite dish (LNB or switch) moves the requested signal to the center of the selected band (**Slot**). Then, the mixing equipment adds each user band (**Slot**) to only one output (up to 32 user bands).





2 Modes :

SATCR : Satellite Channel Router, standard EN50494 (or SCD, Unicable, ...) Distribution of the satellite signal with only one coaxial cable to 2, 4 or 8 different receptors.

SCD2 : Single Cable Distribution v2, standard EN50607 (or SCD2, Unicable II, JESS) Distribution of the satellite signal with only one coaxial cable to a maximum of 32 different receptors. Using DiSEqC 2.0 bi-directional possibility to ask current online devices and speed up installation.

Mode choice: press DCSS



Remote supply - LNB		VDC= 0.8V IDC= 0mA
Remote supply	Triff Off On	
LO frequencies		
LO selection	No	
Polar selection	SATCR (EN50494)	
(Committed) Switch	SCD2 (EN50607)	
Uncommitted Port		
Positioner	No	
DCSS	No No	

SATCR (EN50494) :

Т

emote <u>supply - LNE</u>

Remote supply

LO frequencies

Polar selection

DCSS

(Committed) Switch Uncommitted Port Positioner



- SLOT x: active Slot choice
- CONFIG: access to each slot configuration



9750 MHz / 10600 MHz

SCD2 (EN50607) Slots list, frequencies and switch PosA / PosB

- INITIALISATIONS: 8 predefined slots
- ITALY: 4 predefined slots for Italy
- DETECT: automatic detection of slots (spectrum detect based)

- SLOT x: active Slot choice
- CONFIG: access to each slot configuration

		4 DA 20 4 X 100				00E+ 100.6	
				SCD2 (I	EN50607))	
{e	slot	freq	Pos	Unc	PIN		
.0	-						
0	-						
	-						•
0	-					Allocation	
Ci	-						p. 1
In	-					Detect	
0	-					\checkmark	
Ĩ					4		
D							

📥 Slot 1

Config.

Slots lists, frequencies, switches, PIN codes

INITIALISATIONS : 32 predefined slots

0.72
- ALLOCATION : states of the 32 possible slots
- DETECT : automatic detection of slots (DISEQC2.0 based)

15.2.2.1 Influence of the DCSS on the spectrum analyzer



16 Constellation

The

Constellation

key gives you access to the **CONSTELLATION** function.

These measures are available if one of these standards is running in the **LEVEL MEASUREMENT** page.

- DVB-T/H
- DVB-T2
- DVB-C
- DVB-C2
- DVB-S, DSS, DVB-S2

The appliance displays the **Constellation** of the current signal.

									610.000 MHz
									8k 64QAM 1/8 (auto) 3/4
					*			Alto	BERi : 4.7E-8
	<u>*</u>	-	- Č	*	.	- 	-	<i>1</i>	BERo : < 9E-9
	*	*	M	×	- 	W		*	MER : 33.8dB
	獭	*	-	.		÷.	<u>.</u>	*	
*	*	*	1	*	*	- 1		*	
	*	Ŵ	A	÷.	*	- We	×	- 10	
	*		1	- 18 19	-	- Weight	*		
	*	*	*	Â,		- 1	<i>*</i>	M	

The information displayed on the right of the Constellation diagram is:

- current frequency
- modulation
- constellation
- symbol rate
- error rate and MER



Reminder:

Remember: In terrestrial TV broadcasting, the received signal on the antenna comes from several possible ways: the **echoes**.



In digital TV DVB-T/H and DVB-T2, these echoes may help or degrade the image according to the time delay between the various signals that reach the antenna. The broadcasting norms DVB-T and DVB-T2 define a modulation parameter called "guard interval" where echoes won't disturb the reception.

The transmission of digital data (Symbol) is interrupted during the guard interval.

A delayed (or advanced) symbol of any **shorter** duration than the guard interval will not disturb the reception.

A delayed (or advanced) symbol of any longer duration than the guard interval will disturb the reception.



You have to reduce the level of reception of the echoes by orienting the antenna or by selecting a more directive antenna.

The Echo function of the appliance enables you to display possible echoes that disturb the received signal.



Relative amplitude in dB and delay in μ s (distance in km) from the main signal (0 pulse) can be measured. The yellow line represents the end of the guard interval.

Echoes and pre-echoes (pulses) above the yellow line disturb the signal and must be reduced as much as possible.

The echoes (pulses) beyond this line disturb the reception and must be as weak as possible.



Attention: a high amplitude echo pulse within the guard interval will also disturb the signal quality.

18 Measurement map

To access the **MEASUREMENT MAP** function, press Measurement map:

40	0.7 3.4	E-5	
47	.0 8.9	E-6	Measurement map
42	27 6.2	E-6	

It is an automatic level and error rate measurement of the setups in the measurement list with labeling of the levels beyond tolerance.

	Measure	ment ma	р						VDC= 0.0 IDC= 0m	V A - +
	ST I	TIENNE						1/ 9		
	freq.	std	RF	C/N	BERi	BERo	PER	MER		
Measurement										
result for chan-	► E38	DVB-T/H	51.5	31.1	1.4E-7	<1E-8	<1E-5	33.7		
DVB-T/H	E44	DVB-T/H	49.2	29.3	3.5E-5	<1E-8	<1E-5	32.9		
	E59	DVB-T/H	51.0	31.1	2.3E-7	<1E-8	<1E-5	33.7		
	E40	DVB-T/H	50.9	31.0	4.9E-6	<1E-8	<1E-5	33.1		
	E49	DVB-T/H	52.0	31.6	1.4E-7	<1E-8	<1E-5	33.5		
	E46	DVB-T/H	51.2	30.8	9.5E-8	<1E-8	<1E-5	33.8		
	88.000	FM	57.3	>57.3					\checkmark	

	BERI, BERo and PER are generic terms (frequently used)
Ш.	 BERi = BER in = inner BER first BER treated by the demodulator (BER channel, CBER, LDPC) BERo = BER out = outer BER last BER treated by the demodulator (BER Viterbi, VBER, BCH) PER = packet error rate non-proofread packet, lost packet, wrong packet (UNC, PER)
	Important:
	A bargraph above the Measurement map allows you to track the evolution of the scan.
LL,	The background color of this bargraph shows you that a complete scan has been made (for a save, for example):
	- red: the measurement map has not been totally scanned yet
	green: the measurement map has been totally scanned
U.	In case of mixed measurement map (terrestrial+satellite), the satellite remote power supply has priority (the terrestrial remote power supply is ignored).

18.1 Out of tolerance values

The digital values are colored according to the Thresholds before decision

- red for values less than Threshold min
- orange for values more than Threshold max

Measure	ement ma	ар						VDC= 0. IDC= 0r	nA+
ST	ETIENNE						1/ 9		
fréq.	std	RF	C/N	BERi	BERo	PER	MER		
E38	DVB-T/H	56.3	>22.3	8.6E-4	<5E-9	<5E-6	23.1	\square	
E44	DVB-T/H	56.3	>22.3	9.8E-4	<5E-9	<5E-6	21.9		
E59	DVB-T/H	27.0	>13.0	Sync?	Sync?	Sync?			
E40	DVB-T/H	24.0	>10.0	Sync?	Sync?	Sync?			
E49	DVB-T/H	24.0	>10.0	Sync?	Sync?	Sync?			
623.812	DVB-T/H	60.6	>26.6	Sync?	Sync?	Sync?			
10743 HL	DVB-S	74.7	>20.4	<1E-7	<5E-9	<9E-6	15.3		

19 Optical measurement

19.1 Presentation of the optic measurement

The Optic function allows measurements in various set-up configurations:

-cable satellite reception (cable LNB output)

-after a cable sat/terrestrial coupler

-measurement of optical power

Accessories are provided to use this function:

- -1 angled F/F cable (code: 978754800)
- -1 FC/FC optical fiber jumper cable to switch from APC to PC, SPC or UPC (code: 978754700)
- -1 FC/SC APC optical fiber jumper cable (code: 978754710)
- -1 connection SC/SC APC
- -1 connection FC/FC

Plugging:

(Appliance seen from above)



RF F output of the optical option to connect to the RF F input of the appliance via the provided angled F/F cable

To switch to optical mode:

From the start page:

Sefram		
7859		
Serial number SH01 Version 1.3.1		
Band 5-2200MHz OVB-T/T2/T2-lite DVB-C/C2 DVB-S/S2 Optical input		Optical input

From the home page:

Home	Optical 1310 nm	
RF / optical	Measures-TV-Spectrum	
Lists-Library	Echo guard interval	
Antenna pointing	Constellation	
Check Sat	907 1986 97 1986 97 1986 97 1986	Entrée optique
Autoset	Optical power measurement	
	Configuration	

19.2 What you need to know

A few notions are required before considering the use of optical fibers.

19.2.1 The optical fiber

Optical fibers are sometimes used for satellite reception. This technology enables makes it possible to transmit a signal further with less loss and with a larger bandwidth.

The optical fiber is a waveguide, generally made of glass, that enables the transmission of the optical signal. Optical fibers are made of a core, a cladding and at least one protection. There are two kinds of optical fibers: multimode and single-mode.

The difference is the size of the core inside the fiber: 9µm diameter for single-mode, 50µm for multimode.

Multimode is less expensive, while single-mode induces less losses.

For satellite reception, only single-mode fibers are used.

Sectional view of an optical fiber:





Warning: Optical fibers are fragile and must not be constrained, bent or folded: the core may be damaged or even broken, which results in a partial or total loss of the signal.

19.2.2 Connectors

Like for RF, connectors are very important and their selection has consequences on the quality of the received signal.

With optical fibers, there are several kinds of connectors according to the type of fiber (single-mode or multimode) and to the selected connection.

Thus, there are plastic SC connector for indoor uses and metal FC connectors for indoor and outdoor uses.

Similarly, there are various « polishing » of the fiber core:

- straight PC (Physical Contact) SPC (Super Physical Contact) or UPC (Ultra Physical Contact), or

- angled APC (Angled Physical Contact)

APC polishing generates advantageously less losses by reflection. APC connectors are recognizable thanks to their green color.

If you plug an APC connector to a non-APC connector, in addition to an increased risk of **damaging the connector**, there will be **automatically** a **4dB** decrease of the optical level, which means **8dB** for RF. Thus, you will have to take great care of the connections and the types of connectors for your installation.



On the measurement device, the connector is FC APC, but 2 jumper cables are provided with the appliance to switch from FC APC to FC PC (UPC or SPC) and from FC APC to SC APC.

Ш <mark>г</mark>	<i>Warning:</i> Before connecting a fiber, it is <i>compulsory</i> to clean both connectors with a compressed air spray. Never use clothes, alcohol, water or any other liquid or solvent.
	Warning: The wavelengths inside the optical fibers are generated by lasers; you cannot see them , but they are particularly dangerous for your eyes and may lead to irreversible damages . Thus, you must be very careful when manipulating these fibers (i.e. do not watch inside a connector when linked to the live head). The measurement device has no optical source: it does not emit any light.

19.3 Optical power measurement

To access the Measurement of Optical Power, press the key "Optical power measurement".





Warning: The appliance can measure only one wavelength at a time. If there are several wavelengths, measurements will be wrong.

Plug the optical fiber at the output of your equipment on to the optical FC APC socket of the appliance.

Measurement of the losses at insertion:

Make a first measurement at the LNB of your installation: press the reference of the desired wavelength. The appliance will keep this measure as a reference and automatically switches to dB. Make measurements everywhere on your installation to check losses of the optical signal.

Selection of the displayed wavelength: 1310, 1490 or 1550nm



19.4 The satellite reception via optical fiber

With optical fibers, the satellite emission is the same as in standard reception mode, but at the output of the head, instead of 4 bands (HH HL VH VL), there are only 2 bands (vertical and horizontal) in optical signal mode (the optical head is powered by an independent external power supply).

On your installation, at the end of the fiber, you must install a converter that turns your optical signal to a 4band RF signal: HH HL VH VL; VL and HL bands are between 950 and 1950MHz; VH and HH bands are between 1100 and 2150MHz. Band commutations on this converter are made with 0/22kHz and 13/18V like on any classical installation.

In our case, the output of this head (fiber) may be directly connected to the appliance, which will manage the bands like the converter in order to allocate them between HH, HL, VL and VH. Thus, the use is transparent. **Warning:** the LNB is powered independently.

۳P

Warning: The appliance can measure only one wavelength at a time. If there are several wavelengths, measurements will be wrong.

You'd better check the optical power of the LNB before processing (Measurement of optical power)

To display the signal at the output of your installation, you must connect the RF output of the optical option to the RF input of the appliance via the provided angled F/F cable. Power your LNB (no external power supply is provided with the measurement appliance).

Remove the protective plug from the FC APC optical socket; if required, use the provided jumper cable, and connect the optical fiber from your dish to the same socket.



You can then direct your dish (<u>see chapter 2.2.3 Installation of a dish</u>) Once the measurements are over, **put the protective** plug **on to the optical socket** of the appliance.

19.5 Fiber reception after coupler

The optical option makes it possible to make measurements after terrestrial coupler / sat at the output of the fiber.



Warning: The appliance can measure only one wavelength at a time. If there are several wavelengths, measurements will be wrong.

You'd better check the optical power of the coupler before processing (Measurement of optical power)



To display the signal at the output of your installation, you must connect the RF output of the optical option to the RF input of the appliance via the provided angled F/F cable. Power your coupler (no external power supply is provided with the measurement appliance).

Remove the protective plug from the FC APC optical socket; if required, use the provided jumper cable, and connect the optical fiber from your dish to the same socket.

Then, you can turn your dish (see chapter <u>2.2.3 Installation of a dish</u>) and/or your terrestrial antenna (see chapter <u>2.2.2 Installation of a terrestrial antenna</u>).

Once the measurements are made, put the plug onto the optical socket of the appliance.

20 Configuration

For configuration, go to the Home page, then Configuration

Home	Optical 1310 nm	Configuration		-
RF / optical	Measures-TV-Spectrum	Language: English	Seep: 50%	
💒 Lists-Library	Echo guard interval			
Antenna pointing	Constellation	IP address: 192.168.	0.170 Europe	
Check Sat	107 1865 178 1866 Measurement map	Memories 4 / 7.494%	%	
Autoset	Ontical nower measurement	📎 🔸 Configuration imp	port 🔹 🍋 Configuration export	
	Configuration	Factory recovery	Software update	

20.1 Language

You can select your language by pressing the « flag » (below). Press the flag corresponding to your language:

Configuration	Configuration Vice and IBC and	
Language: English Seep: 50%	Language: E Language	
IP address: 192.168.0.170 Frequency map Europe	IP address: 1 Français Deutsch	. Ya 🖩
Memories 4 / 7.494%	Memories 4	
Configuration import	Configura	
Factory recovery Software update	Factory recovery Software update	

20.2 Frequency map

This key allows you to select the terrestrial frequency map of the appliance:

Configuration	Configuration	Fraguasau man	VDC= 0.0V IDC= 9mA
Language: English Seep: 50%	Language: English	France	
IP address: 192.168.0.170 Frequency map Europe	IP address: 192.168.	France Cable	map
Memories 4 / 7.494%	Memories 4 / 7.494	Italia	
Configuration import	Configuration imu	OIRT Australia	ation export
Factory recovery 📎 🖓 Software update		Korea 🗸	
	Factory recovery		tware update

20.3 Memories

To save a picture or any other feature, see chapter <u>Save</u> The number of saved file and their memory size are displayed.



When pressing this key, a pull-down menu lists the previously saved files.

The first column contains the order number of the file; the second column contains the name of the file; the last column contains the type of file: Measure, Spectrum, Measurement map...

Config	<u>,</u>	<u>In en</u>		Files list	VDC= 0	
	0	0	MEM0.TXT	Measures		
	0	1	MEM1.TXT	Spectrum		
m.	0	2	MEM2.TXT	Constellation		
	0	3	МЕМЗ.ТХТ	Measurement map		
					<u> </u>	
					\checkmark	
F						

By pressing a line of the table, you open a window:





20.3.1 View

This key allows the display of the content of the file:



20.3.2 Save

Save (BMP -> USB) allows you to export the file to the USB stick under BMP format (non-compressed graph); it is useful to transfer graphs to a report in a PC computer.

Here is the BMP file of the previously displayed DVB-T/H channel, edited on PC to have the spectrum full screen.



- <u>Save (CSV -> USB)</u> allows you to export the file to the USB stick under CSV format (text file by columns separated with semicolons); it is useful to analyze values in a spreadsheet.

Here is the spectrum here above with a curve under EXCEL™.



- <u>Save all (BMP -> USB)</u> records all files from the appliance under BMP format into separated registers:

- LEVEL for the level measurements
- MAP for the measurement maps
- SPECTRUM for the spectrum measurements
- BER-MER for the error rate measurements
- CONST for the constellations
- ECHO for the echoes.
- <u>Save all (CSV -> USB)</u> also records all files from the appliance into separated registers, but under CSV format.

20.3.3 Update

See chapter Software update for more details.

- 7859 -

20.4 Factory recovery

A complete set-up of the appliance under its FACTORY configuration, with confirmation







20.5 Configuration import/export

You can make a backup on a USB stick of your setups/lists of your appliance by pushing « « Configuration Export ».

And you can import from a USB stick this configuration with the touch "Configuration import". You can also update checksat/antenna pointing configuration available on SEFRAM's website: <u>http://www.sefram.com/telechargement/fichier-de-configuration.html</u>

21 Software update



Attention: Take care that the remaining battery life is sufficient (> 30%), else plug the appliance on the mains with the provided adapter.

You can easily update the software to get new functionalities.

The update requires an USB stick.

To achieve the update:

- Download the update file 784X_VX.X zip file on our website (www.sefram.fr)
- Insert a USB stick on your PC
- Unzip the file onto the root of the memory stick
- Pull the USB stick off from your computer
- Turn your appliance on

- Go to the Home page, press configuration - Insert the USB stick into the connector of the appliance.

- Select Update: Software update



The updating process lasts ca. 10 minutes. At the end of the update, the appliance asks you to restart the appliance. The software is then loaded into your appliance.

Error messages may show up: Do not take them into account.

22 Save

Pressing

I opens a window (here, on the Measurement page):



In this window, you can save the current measurement parameters from the active list, make a screen shot to a USB stick under BMP format or make a save into internal memory.

You can rename the save file (see chapter Man-machine interface).

The default name of the save is MEM(X+1) (X is the number of saves in the appliance).

You will be suggested a save into internal memory only in the **Spectrum, Measurements, Constellation, Guard interval** and **Measurement map** pages.



After transfer, you will be able to use the saved measures to create measurement reports on your computer (see paragraph <u>Saves</u> for more details).



When you stop the appliance, it may need a few seconds to stop completely because the save on flash memory is carried out during the extinction.

23 Connection of the appliance to a PC

The appliance has an ETHERNET interface that makes it possible to connect directly to a PC.

For this type of connection, no driver is necessary.

Connect your appliance to your PC by using a crossed ETHERNET cable (available in option with the number 298504246 asking SEFRAM).

and:

Configuration of the connection:

Ethernet connection of your appliance to the PC.

To change the IP address of your appliance, press





The PC software in communication with the appliance must have the same IP address as the appliance, just like in the example below:



p. 93



<u>Attention</u>: If the PC has already been connected to Ethernet (network, modem...), it is necessary to reboot the PC before connecting your appliance.

For the **Ethernet** connection of your appliance to a computer network, see the following scheme:

1) Contact your network adminis- trator to get a free IP address and the subnet mask	2) Type the IP address and the subnet mask in the app ance		address and sk in the appli-
3) Type the same IP address and subnet mask in the PC software you're using			

24 Displayed messages

The appliance may display messages while working.

24.1 Alert messages

Low battery: the appliance is about to shut off in a few minutes.



Confirmation request for an important action.

ContCo	onfiguration voc- o).OV ImA
Lani	Language: English Seep: 50%	
Date 🤍		
Expe	IP address: 192.168.0.170 Frequency map	
Unit	Please confirm	
Freq 🚽	Memories 4 / 7.4 Yes No	
Men		
Adju	Configuration import	
Fact	Factory recovery Software update	

Remote power supply issue: voltage already present or maximum current exceeded.



Remote supply - LNB				VDC= 0.0V IDC= 9mA	:
Remote supply	110 The	0n			
LO frequencies	0750	NH- 1 1060()			F
LO selection	\bigcirc	OFF			
Polar select 🕂 Remote :	supply fault: p	ower supply	already prese	ent	
(Committed) Switch					
Uncommitted Port					
Positioner	× No				
DCSS	X No				

Messages of the same kind may show up; the pop up window is an alert; the corresponding message explains the issue.

24.2 Error messages

A message may show up at the bottom of the screen immediately after updating the software. Do not take it into account as far as it does not show up at a second start-up.

Else, or for any other problem, contact the **SEFRAM** technical support:

- e-mail: support@sefram.fr
- > <u>Telephone</u>: 04 77 59 01 01

25 Maintenance

This appliance requires some maintenance to meet its requirements and maintain its general characteristics.

	Consequences	Recommended periodicity of con- trols	Recommended use limit
BATTERY	Reduction of the bat- tery life		200 charge / dis- charge cycles or 2 years
STRAPS	Breakdown	At each use Check the holding of the straps	
Back Light SCREEN	Reduction of visibility		1 year
Measurement setting / check	Erroneous measures	Once a year	12 months
CONNECTIONS	Erroneous measures	At any measurement	
Optical fiber jumper cable	Erroneous measures	At any measurement, check the state and cleanliness of the jumper	

This "advice" does not engage the responsibility of SEFRAM I.S.

It guarantees the best possible use of the characteristics and the preservation of the product.

Routine maintenance:

The basic maintenance is simply cleaning the outside of the appliance. Any other operation requires a trained personal.

Unplug the appliance before any intervention.

Do not let water flow inside the appliance: risk of electric shock.

Periodically clean the appliance under the following conditions:

- use soapy water
- never use any product containing petrol, benzene, alcohols that would attack silkscreen printings
- wipe out with a soft lint-free cloth
- use a solvent-free antistatic product to clean the screen.

RF socket:

- Make sure there are no specks of copper between the winner conductor and the ground
- Replace periodically the adapter F/F, an adapter in poor condition distorts all the measures.

Optical:

- Before connecting a fiber, it is compulsory to clean both connectors with a compressed air spray. Never use clothes, alcohol, water or any other liquid or solvent.

INFORMATION ABOUT THE LCD COLOR SCREEN WITH ACTIVE MATRIX

Your SEFRAM field strength meter is equipped with a LCD color screen with active matrix.

This screen is provided by renowned manufacturers. In the current technical conditions of manufacture, they cannot guarantee 100% good functioning pixels in the display zone. They specify a number of possible defective pixels at the surface of the screen.

The SEFRAM quality service has preconditioned the mounting of the screen on your instrument to the respect of the acceptance conditions of the manufacturers.



Acceptance criteria:

Zone A (central zone): total less than 5 defective pixels, less than 3 contiguous pixels.

Zone B (total surface of the screen): less than 9 defective pixels on the whole surface of the screen, with respect of the conditions prevailing in zone A.

Is considered as defective any pixel on screen that does not light up or lights up in a different color as expected.

The contractual guarantee on your field strength measurer can be exerted only if these criteria are not met, as well at delivery as during the period of guarantee.

26 Technical specifications

26.1 Technical specifications

Technical specifications	Terrestrial band	Satellite band	
Frequencies			
Range	5-900 MHz	900-2200 MHz	
Resolution	measure 50 kHz, display 1 kHz	measure 1MHz, display 1MHz	
Level measurements			
Dynamic range	20-120 dBµV (30-120 dBµV for 5-45MHz)	30-110 dBµV	
Noise floor level	10 dBµV typical	20 dBµV typical	
Units	dE	μV	
Accuracy	±2dB +/-	0.05dB/°C	
Resolution	0,1	ldB	
Measurement Filters	100KHz - 300 kHz - 1MHz	1MHz - 3MHz - 10MHz	
Standards	DVB-C/C2, DVB-T/T2/T2lite BG, DK, I, L, MN, carrier	DVB-S/S2, DSS PAL, SECAM, NTSC	
Measures	RF level/p	bower, C/N	
Spectrum Analyzer			
Fast Mode	350 ms typ	. (3 times/s)	
Filters (according to span)	100kHz, 300kHz, 1 MHz	1MHz - 3MHz - 10MHz	
Attenuator	automatic or manual (0 to 55 dB with 5 dB step)		
Dynamic range (display)	60 dB (10 dB/div)		
Span	5MHz à full span 1, 2, 5 step		
Pre-echoes /Echos DVBT/T2			
Dynamic range	DVB-T : 50 dB, -75km +75km (8k) DVB-T2 : 50 dB, -75km +75km (8k) DVB-C2 : 50 dB, -35km +35km (4k)		
Units	μs, km, miles		
Constellation display			
	yes, standards DVB-T/T2,	DVB-C/C2, DVB-S/S2, DSS	
Measurement Map			
Capacity	scanning of 50 s	setups maximum	
Display	Text table		
TV MPEG			
Digital Multiplex (not coded)	MPEG2 SD (définition standard) MPEG4 HD (haute définition H.264)		
Service table DVB-SI	SDT	SDT, LCN	
Sound	MPEG-1, MPEG-2, AAC, HE AAC, Dolby® Digital, Dolby® Digital Plus		

26.2 Digital measurements

DVB-T/H	
Bit Error Rate (BER)	CBER (before Viterbi BERi) VBER (after Viterbi BERo) UNC (lost packets PER) Noise margin
Modulation Error Rate(MER)	5 - 35dB
Bandwidth	6MHz, 7 MHz, 8 MHz
FFT type	2k, 8k, auto
Constellation	QPSK, 16QAM, 64QAM, auto
Viterbi rate	1/2, 2/3, 3/4, 5/6, 7/8, auto
Guard interval	auto, manual
Spectrum inversion	auto
HP/LP – PLP – Data Slice	HP/LP
Standards	ETS 300-744

DVB-T2 / T2 Lite	
Bit Error Rate (BER)	LDPC (BERi) BCH (BERo) FER (frame error PER) Noise margin
Modulation Error Rate(MER)	5 - 35dB
Bandwidth	1.7MHz, 5MHz, 6MHz, 7 MHz, 8 MHz
Mode	SISO, MISO, PLP single or multiple
FFT type	1k, 2k, 4k, 8k, 16k, 32k + extended bandwidth, auto
Constellation	QPSK, 16QAM, 64QAM, 256QAM, auto
Viterbi rate	1/2, 3/5, 2/3, 3/4, 4/5, 5/6, 1/3, 2/5, auto
Guard Interval	auto
Spectrum inversion	auto
HP/LP – PLP – Data Slice	PLP
Standards	ETS 302-755

DVB-C J83A	
Bit Error Rate (BER)	BER (before Reed Solomon BERo) UNC (lost packets PER) Noise margin
Modulation Error Rate(MER)	20 - 40dB
Symbol Rate	1 to 7.224 Ms/s
Constellation	16QAM, 32QAM, 64QAM, 128QAM, 256QAM
Spectrum inversion	auto
Standards	ETS 300-429

DVB-C2	
Bit Error Rate (BER)	LDPC (BERi) BCH (BERo) FER (frame error PER) Noise margin
Modulation Error Rate(MER)	5 - 35dB
Symbol rate	-
Bandwidth	6MHz, 8 MHz
Mode	PLP and data slice, single or multiple
FFT type	4k
Constellation	16QAM, 64QAM, 256QAM, 1024QAM, 4096QAM, auto
Viterbi rate	2/3, 3/4, 4/5, 5/6, 8/9, 9/10

Guard interval	auto
Spectrum inversion	auto
HP/LP – PLP – Data Slice	PLP+Data Slice
Standards	ETS 302-769

DVB-S, DSS	
Bit Error Rate (BER)	CBER (before Viterbi BERi) VBER (after Viterbi BERo) UNC (lost packets PER) Link margin
Modulation Error Rate(MER)	0 - 20dB
Symbol rate	1 to 45Ms/s
Constellation	QPSK
Viterbi rate	1/2, 2/3, 3/4, 5/6, 6/7, 7/8, auto
Spectrum inversion	auto
Standards	ETS 300-421

DVB-S2	
Bit Error Rate (BER)	LDPC (BERi) BCH (BERo) PER Link margin
Modulation Error Rate(MER)	0 - 20dB
Symbol rate	1 to 45Ms/s
Constellation	QPSK, 8PSK, 16APSK, 32APSK
Modulation	CCM, VCM, ACM
Multistream	stream select ISI 0-99, PL scrambling (Gold code)
Viterbi rate	2/5, 1/2, 3/5, 2/3, 3/4, 5/6, 8/9, 9/10, auto
Spectrum inversion	auto
Standards	ETS 302-307

26.3 OPTIC MEASUREMENT

Measurement of optical power	
Bandwidth	1310nm, 1490nm, 1550nm
Measurement dynamics	-49.9dBm to +10dBm
Accuracy	+/- 0.5dB
Connector	FC/APC
Optical converter	
Conversion dynamics	-5dBm to +10dBm
Converted RF band (cable)	50 to 900MHz
Converted RF band (optical LNB)	950MHz to 5450MHz
Output RF bandwidth	50MHz to 2150MHz
Output connector	F

26.4 Miscellaneous

Remote supply	Terrestrial	Satellite		
Voltage	5V/13V/18 V/24V 500 mA max (300mA for 24V)	13/18 V 500 mA max		
DiSEqC	-	DiSEqC 1.2 control of dish motor switches committed & uncommitted		
Mini DiSEqC (22kHz)	-	22 kHz, ToneBurst		
SCD /SATCR EN 50494 Single cable satellite distribution	-	8 slots max switch committed		
SCD2 EN 50607 Single cable satellite distribution v2	- 32 slots max switches committed & uncommitted code PIN			
Storage				
Memory	Internal on non-volatile memory, or external USB stick (not supplied)			
Data saved	measurements (level, BER/MER, Measurement Maps, Spectrum,)			
Capacity	512 KB (about 150 files)			

Inputs / Outputs	
RF input	75 Ohms, F (with adaptor)
Max permitted voltage	48V RMS / 50Hz
Interfaces	USB A, USB mini B, Ethernet 10baseT (RJ45)
DC supply input	jack 5.5 mm 15 V max, 5 A max

Display	LCD TFT 7 inch color 16/9, luminosity backlight 500 cd/m ² , 800x480 dots Touch capacitive		
External supply	Main adaptor 110/230 VAC, with 5,5mm jack, 15 V 1 A		
Battery	Batterie Li-ion 25W		
Autonomy	2 hours typical, depending of use		
Charging time	1,5 hour for 80% of capacity		
Operating temperature	-5°C to 45°C		
Storage temperature	-10°C to 60°C		
EMC and safety	fety NF EN 61326-1(2013) et NF EN 61326-2-1(2013) (class B, basic electromagnetic environment) / NF EN 61010		
Dimensions	250 x 165 x 65 mm		
Weight	1,350 kg		

26.5 General specifications

26.6 Accessories

Supplied with: main adapter, battery (installed), user manual (CD-ROM), F/F adapter, pouch with carrying belt and dedicated accessories for optical input (<u>Presentation of the optical measurement</u>)

Optional accessories:

٠	Car cigar lighter adaptor:	ref. 978361000
•	Carrying bag 784X/781X:	ref. 978481000
•	Luxury backpack	ref. 978751000
•	Sun protector + Rain protector + coat hook	ref. 978489000
•	Rain protector	ref. 978489500

Contact our sales department SEFRAM.

04 77 59 01 01

26.7 V, dBµV, dBmV and dBm conversion

 $dB\mu V$ (dBm V) is a logarithmic ratio between a measured voltage Ud and a reference voltage Ur. The reference voltage is Ur = 1 μV (1 mV)

N = 20 log (Ud/Ur)

dBm is a logarithmic ratio between a measured power Pd and a reference power $\ensuremath{\mathsf{Pr}}$.

The reference power is Pr = 1 mW into 75 ohms.

 $N = 10 \log (Pd/Pr)$ with Pd = Ud2 / 75

$U_{d} = 1 \ \mu V$	$N = 0 dB\mu V$	N = - 60 dBmV	N = -108.75 dBm
$U_d = 1 \text{ mV}$	$N = 60 \text{ dB}\mu V$	N = 0 dBmV	N = -48.75 dBm
$U_d = 1 V$	N = 120 dBµV	N = 60 dBmV	N = 11.25 dBm

26.8 Typical values for measurements

Values given are indicatives, minimum and maximum for good signal quality

Measurements	Level, power (dBµV)			DED		modulation
	mini	maxi	(dB)	BEK	(dB)	modulation
Terrestrial						
Analogue TV	57	74	> 45	-	-	-
FM	50	66	> 38	-	-	-
DAB/DAB+	35	70		BER < 2 ^E -4	-	2K
DVB-T/H	35	70	> 26	VBER < 2^{E} -4	> 26	8K, 64QAM, 1/32, 2/3
DVB-T2	35	70	> 22	FER < 2 ^E -7	> 22	32K, 256QAM, 1/8, 2/3
DVB-C	57	74	> 31	BER < 2 ^E -4	> 31	64QAM
Satellite						
Analogue TV	47	77	> 15	-	-	-
DVB-S, DSS	47	77	> 11	$VBER < 2^{E}-4$	> 11	QPSK, 3/4
DVB-S2	47	77	> 8	PER < 1 ^E -7	> 8	8PSK, 2/3

27 Terminology

$2\kappa/8\kappa$: The number of carrier waves of the DTT channel

The **8K** mode (6817 carrier waves in the channel, including 6048 carrying useful data) The **2K** mode (1705 carrier waves in the channel, including 1512 carrying useful data) For the same purpose, the 8K mode allows the selection of a larger guard interval than the 2K mode, thus a better resistance to echoes

SPECTRAL ANALYSIS : Method used to highlight the characteristics of the signal. The interest of this analysis is to visualize the troublemakers as well as the shape of the signal. The spectrum analysis highlights the amplitude frequency characteristic.

FREQUENCY BAND : Continued portion of the frequency spectrum having made the object of a particular affectation (telecommunication, television, internal security...)

Example: UHF band \rightarrow 470 to 860 MHz

BCH : Bose Chauhuri Houquenohem

Algorithm used to correct errors in transmissions of digital satellite DVB-S2 signals.

BER: Bit Error Rate

Calculation of the erroneous bits with regard to the number of transmitted bits. BER demonstrates the degradation of the digital information.

V PACKAGE : Set of channels spread and marketed by a same operator (TPS, Canal Satellite...)

<u>CHANNEL</u>: Assignment of a number to the transmission frequency of an audio video signal. TV channels receive numbers. Specific to each country.

Example: from 21 to 69 for the UFH band

canal 21 = frequency 471.25 MHz

CELL ID: Cell identification

Identification of the DVB-T emitter with 4 digits in hexadecimal format, which means 65536 possibilities.

C/N: Carrier to Noise ratio

A good C/N ratio helps the quality of the pictures on the TV screen. Ratio in dB. Caution: You have to take the ratio analysis filter width / channel into account.



COFDM: Coded Orthogonal Frequency Division Multiplex.

Digital coding used for DTT. Its principle is to transmit information via many carrier waves (2K or 8K mode).

CONSTELLATION: Control mean for the quality of the signal by a group of points making spots on the screen of

the field meter. The more circular and distinct the spots of the constellation, the better the quality of the

signal. In addition, according to the shape of the spots, you can evaluate the kind of error. This function is available on field meters that enable the display of the constellation for any type of digital signal QAM, QPSK

and COFDM.

Typically:

-QAM (cable) : 64 spots (16 spots per quarter) -COFDM (TNT) : 64 spots (16 spots per quarter) -QPSK (Satellite) : 4 spots (1 spot per quarter) -8PSK (Satellite) : 8 spots (on a circle)





COUNTER-POLARIZATION: Ratio between the levels received from the desired polarization and the opposed polarization (it should be as high as possible). To adjust the counter-polarization, you have to turn the head of the dish.

DAB: Digital Audio Broadcasting.

The Digital Audio Broadcasting is a standardized audio broadcasting system (coded in COFDM). It exists on the following bands:

L Band: 1452-1492Mhz

3 Band: 223-230Mhz

DVB-T: Broadcasting norm for the terrestrial digital television, COFDM modulation

DVB-C: Broadcasting norm for the cable digital television, QAM modulation

DVB-C2: Broadcasting norm for the cable digital television by cable (based on DVB-T2)

DVB-S: Broadcasting norm for the satellite digital television, QPSK modulation

<u>VB-S2</u>: Broadcasting norm for the satellite digital television, QPSK or 8PSK modulation

DISEQC: Digital Satellite Equipement Control.

Control norm for the equipment of reception for satellite signals. Uses a 22kHz signal superimposed to the

remote supply voltage of the satellite dish.

FREQUENCY: Parameter that characterizes the radio-electrical wave. It is measured in "Hertz". We usually use

some multiples of this unit: kilohertz (kHz), megahertz (MHz), gigahertz (GHz).

ex.: At Saint Etienne (Guizay), the TF1 frequency is 583.25 MHz

HP/LP: high/low priority → possibility to transmit 2 multiplexes under the same channel in digit format (ex.: in COFDM, we have a very robust high priority flow in QPSK; secondary flow in 16QAM)

GUARD INTERVAL: The guard interval is the time when the signal is not emitted: all signals carrying the same

information but coming from different sources (various emitters or through multiple reflections) won't disturb

each other.

Value for DTT: 1/32 (28 μs), that permits echoes lower than 8.4km

SOFREQUENCY: (or SFN: Single Frequency Network)

A DVB-T emitter network that emits on a whole region or a country at the same frequency.

 \rightarrow risk of echoes outside the guard interval

 \rightarrow moving reception

NB: Low Noise Block-converter

A LNB (or universal head) is a standard converter for the analogical and digital reception of a satellite.



The reception is made on 2 low/high frequency band and 2 horizontal/vertical polarizations of the received wave.

The commutation of the band is made by a 13/18Volt voltage. The commutation of the polarization is made by a 22kHz signal superimposed to this voltage (you can also use the DiSEqC commutation for some LNB).

______ Low Density Parity Checker

An algorithm used to correct errors in transmissions of digital satellite transmissions DVB-S2 signals.

NOISE MARGIN: Difference between the measured and the theoretical noise level before incorrigible errors.

Difference in dB between the measured C/N and the minimum C/N for error-free transmission.

MER: Modulation Error Ratio

Ratio in dB measuring the distance between the theoretical dot and the observed dot on a constellation quarter. You can use it to control the reception: **the higher this value, the better the image**.

Error vector Magnitude vector (from the reference dot to the ideal dot)

MODULATION: Once the signal has been coded, it is modulated with a carrier wave for transmission. AM (Amplitude Modulation): analogical modulation of the amplitude of the carrier wave

FM (Frequency Modulation): analogical modulation of the frequency of the carrier wave

QPSK (Quadrature Phase Shift Keying): phase digital modulation

QAM (Quadrature Amplitude Modulation): phase and amplitude digital modulation

COFDM (Coded Orthogonal Frequency Division Multiplex): phase and amplitude digital modulation on multiple carrier waves; for DTT.

MPEG: Motion Picture Expert Group

MPEG is a family of compressed digital coding formats for audio / video. The aim of MPEG coding is to hugely reduce the amount of transmitted information with as little loss as possible thanks to very complex compression algorithms.

The MPEG 2 option on the SEFRAM field meters allows you to view and control TV programs (coded under MPEG) directly on the meters.

ex.: On the Astra satellite, the EURONEWS and SPORT + channels are non-encrypted and visible on the field meters.

WULTIPLEX: Set of channels broadcasted by the same operator (smaller set than a package). In DTT, a

multiplex has a 24.5Mbits/s flow rate. A multiplex enables the diffusion of 6 programs in standard definition

NIT : Network Information Table – Information about the network/package

Enables the display of a description of the measured transponder. The information is sent non-coded in the data flow from the QAM, COFDM or QPSK decoder. The information items are:

- Name of the operator
- List of the transponders of the package
- Orbital position of the satellite (in Satellite mode).

OFFSET: The central frequency of a DTT channel may be shifted by ± 166.7 kHz in case of adjacent analogical channel to prevent disturbances

OL: A local oscillator that converts the frequency received from the satellite, in GHz, into an intermediary frequency that the demodulator can use, in MHz.

ex.: a 11.778 GHz frequency from the satellite passing through a 10.6 GHz OL LNB becomes a 11.778-10.600=1.178 MHz

See LNB scheme.

AUDIO AND VIDEO PID: Packet Identifier. MPEG service information.

In the digital MPEG flow, the (audio or video) packets all include a PID to get binary data from each service.

Frequency plan: There are various Frequency Plans according to places and standards. In the SEFRAM

field meters, the frequency plans are pre-programmed: they gather the most frequently used frequency bands.

Measure map: Allows the simultaneous view of characteristics (frequency, channel, standard...) of various programs (TF1, France2...) with location of measures except tolerance. Allows to carry out BER level measures, for a list of programs.
PLP: (Physical Layer Pipe) from 1 to 256 channels are available in DVB-T2 to transport independent multiplexes.

POLARIZATION: Polarization of a signal from the satellite. It can be either:

linearly polarized, horizontally or vertically:

Circularly polarized to the right or the left





In ground reception, the polarization is generally horizontal (the stalks of antennas are horizontal). Some receptions in band VHF are in vertical polarization (Canal+). In this case, the stalks of the antenna are vertical.

POSITIONER: A motorized system for the rotation of a satellite dish. Positioners are operated by DiSEqC commands

QAM : Quadrature Amplitude Modulation.

This kind of modulation is used for digital transmissions (cable networks and DTT).

QPSK: Quadrature Phase Shift Keying (or 4PSK) A kind of modulation mostly used for satellites.

ΒPSK: A type of modulation identical to QPSK, but with an 8-possibility (3-bit) coding. This kind of modulation enables

higher rates than QPSK and is compatible with DVB-S2.

REED-SOLOMON: An algorithm used to correct errors in digital transmissions

STANDARD: Any norm that defines the characteristics of a modulation. Analogical standards: L, BG, DK, etc. Digital standards: QAM for **cable television** QPSK, 8PSK for **satellite television** COFDM for **terrestrial digital television** **<u>T-DMB**</u>: A digital broadcasting system based on the DAB.

This very robust broadcasting mode for mobile applications thanks to the modulation used (DQPSK=differential QPSK). Allows the reception of digital television but also of television programs on

small-size appliances like mobile telephones or PDA

<u>Тор ре зумснко :</u> Signal carré indiquant le début d'une trame ou d'une ligne.

VHD : Télévision Haute Définition

En télévision standard, le nombre de lignes composant l'image va de 480(NTSC) à 576 (PAL et SECAM). Chaque ligne comprend 720 pixels. Pour comparer à l'informatique, un téléviseur correspond à une résolution SVGA 800 x 600. La proportion de l'image est de 4/3 (rapport largeur / hauteur).

En télévision HD, l'image est constituée de 1080 lignes, chacune constituée de 1920 pixels – soit un équivalent de 2M pixels.

Les téléviseurs HD ready ont une résolution minimale de 1280 par 720

Les téléviseurs Full HD ont une résolution minimale de 1920 par 1080

UNC : un-corrected packets

VIACCESS - MEDIAGUARD : Decryption systems used in Europe by many operators (TPS, Canal Satellite...).

With the Viaccess and Mediaguard options in a SEFRAM field meter and your subscription card, you will be

able to view encrypted programs on the meter.

VITERBI : An algorithm used to correct errors in digital transmissions